

WPH/WGH SERIES

POLYCARBONATE/GLASS
WALLPACKS

Cat. #		Approvals
Job	Type	



APPLICATIONS



- Perimeter lighting.

SPECIFICATIONS

- WGH metal halide fixtures feature borosilicate glass refractor for non-yellowing. WPH HPS units have polycarbonate refractors for vandal resistance. Stainless steel Phillips head screw closure.
- Cast aluminum housing with 1/2" conduit and photocontrol hubs. Box mounting adapter included.
- 4-to-1 spacing ratio...has two mounting height forward projection.
- 70 and 100 watt HPS and metal halide. Lamp included.
- Medium base porcelain sockets.
- Dark bronze powder paint finish.

LISTINGS

- UL 1598 listed for use in wet locations.



A	B	C
8 1/2"	8 1/2"	8 1/2"
216 mm	216 mm	216 mm



ORDERING INFORMATION

Catalog Number ¹	Wattage/Voltage	Finish	Start Temperature	Weight	
				lbs	kg
HIGH PRESSURE SODIUM					
WPH-100S	100 HPS/120V	Bronze	-40°F	9	4.1
WPH-70S	70 HPS/120V	Bronze	-40°F	8	3.6
PULSE START METAL HALIDE					
WGH-100H	100 MH/120/208/240/277V	Bronze	-20°F	10	4.5
WGH-70H	70 MH/120/208/240/277V	Bronze	-20°F	9	4.1

¹ Lamp included on all units.

ACCESSORIES

(order as separate part #)

Catalog Number	Description
PBT-1	Button photocontrol 120V
PBT-234	Button photocontrol 208, 240, 277V

PHOTOMETRIC REPORTS

Catalog Number	Report #
WPH-100S	HP08271.IES
WGH-100H	HP08272.IES

Due to our continued efforts to improve our products, product specifications are subject to change without notice.



Outdoor Lighting

Hubbell Outdoor Lighting • 701 Millennium Boulevard • Greenville, SC 29607 • PHONE: 864-678-1000

For more information visit our web site: www.hubbell-ltg.com