


## POWER & EFFICIENCY

INPUT POWER OPTIONS	AC 1PH 200-240V 60Hz   AC 3PH 200-240V 60Hz   AC 3PH 380-480V 60Hz		
MAXIMUM RATED CURRENT (amp)	5.4 - 4.5 A		2.8 - 2.4 A   1.2 - 1.0 A
POWER (hp)	3/4 hp		
MAXIMUM SPEED (RPM)	103 RPM		
MAX AFFECTED AREA	88 ft Dia   7,744 sqft		

## DIMENSIONS & WEIGHT

FAN DIAMETER	14 ft
FAN WEIGHT	168 lb (76 kg)
	

## MOUNTING & SAFETY

MOUNTING OPTIONS	I-beam   Glulam
DOWNROD (A)	Downrods available in 1 ft increments: 2 ft min., 10 ft max. Downrod length must be specified at time of order.
SAFETY FEATURES	Fan Retention System   Airfoil Retention System   Fire relay

## IN THE BOX

INCLUDED	Fan I-beam mount with pre-wired downrod   Control panel   Install manual Mounting hardware kit   Communication Kit   Guy wire kit
OPTIONAL	Additional cable lengths   Touchscreen (5 in)   Glulam brackets

## WARRANTY & CERTIFICATIONS

CERTIFICATIONS	ETL/Intertek-certified to ANSI/UL 507 and CSA C22.2 No. 113 in North America
WARRANTY <sup>1</sup>	15-year, Non-Prorated Warranty

<sup>1</sup>See complete warranty for details.