


POWER & EFFICIENCY

INPUT POWER OPTIONS	AC 1PH 200-240V 60Hz AC 3PH 200-240V 60Hz AC 3PH 380-480V 60Hz		
CURRENT AT MAX SPEED (Amp)	7.2 - 6.0 A		4.0 - 3.3 A 2.6 - 2.2 A
POWER (hp)	1 hp		
MAXIMUM SPEED (RPM)	74 RPM		
MAX AFFECTED AREA	125 ft Dia 15,625 sqft		

DIMENSIONS & WEIGHT

FAN DIAMETER	20 ft
FAN WEIGHT	190 lb (86 kg)
	
Pictured with 2 ft downrod	

MOUNTING & SAFETY

MOUNTING OPTIONS	I-beam Glulam
DOWNROD (A)	Downrods available in 1 ft increments: 2 ft min., 10 ft max. Downrod length must be specified at time of order.
SAFETY FEATURES	Fan Retention System Airfoil Retention System Fire relay

IN THE BOX

INCLUDED	Fan I-beam mount with pre-wired downrod Control panel Install manual Mounting hardware kit Communication Kit Guy wire kit
OPTIONAL	Additional cable lengths Touchscreen (5 in) Glulam brackets

WARRANTY & CERTIFICATIONS

CERTIFICATIONS	ETL/Intertek-certified to ANSI/UL 507 and CSA C22.2 No. 113 in North America
WARRANTY ¹	15-year, Non-Prorated Warranty

¹See complete warranty for details.