

# BREATHING WALL-ECO CARAT

Rooted in traditional Japanese mud-wall construction, ECO CARAT is a sublime collection of interior wall tiles that combine natural materials and colors with exquisite patterns to impart a sense of unparalleled beauty and relaxation. Defined by design and technology excellence, ECO CARAT features moisture-regulating and odor reducing properties to help enhance indoor comfort.



**ROUGHSAWN**  
A relief finish that looks like roughly cut wood

ECP-275NET-RGS-3

APPLICATIONS (Interior Dry Wall ONLY)								
LIVING ROOM WALL	BEDROOM WALL	ENTRANCE WALL	HALLWAY WALL	RESTROOM	EXTERIOR WALL	BATH/SHOWER WALL	FLOOR	KITCHEN BACK
Yes	Yes	Yes	Yes	Yes <sup>1</sup>	No	No	No	No

<sup>1</sup>. Above waste/water line

COLOR VARIATIONS*2			
V1	V2	V3	V4

\*2. Please note: variations in color, shade, surface texture and size are natural characteristics of all our products and should be expected. Images shown are representative, but may not indicate all variations in these characteristics.

## FIELD



ECP-275NET-RGS1  
White




ECP-275NET-RGS2  
Beige



ECP-275NET-RGS3  
Light Brown

<b>Material:</b>	Porous ceramics/Glazed
<b>Size/Piece:</b>	24.25 x 74.75mm (.96 x 2.94 in)
<b>Size/Sheet:</b>	302 x 302mm (11.89 x 11.89 in)
<b>Thickness:</b>	6mm, 8.5mm Mix
<b>Joint:</b>	1mm Open joint
<b>Sq. Ft/Carton:</b>	10.47
<b>Sheets/Carton:</b>	11
<b>Mounting:</b>	Back net-Paper
<b>Weight/Carton:</b>	26.9 lbs

## TRIM/CORNERS



90° External Corner  
ECP-275N-9014-RGS1...RGS3

Installation for corner  
(External)



<b>Material:</b>	Porous ceramics/Glazed
<b>Size/Piece:</b>	(24.25+24.25)x74.75mm *(.95+.95)x2.94 in
<b>Size/Sheet:</b>	(25.25+25.25)x303mm *(.99+.99)x11.9 in
<b>Thickness:</b>	6.0mm
<b>Joint:</b>	1mm Open joint
<b>Ln. Ft/Carton:</b>	3.85
<b>Sheets/Carton:</b>	11
<b>Mounting:</b>	Back net-Paper
<b>Weight/Carton:</b>	1.32 lbs

# INSTALLATION

BASE MATERIAL SUITED		EXISTING WALL FINISHES		OTHER PRECAUTIONS	
Material:	Suitable	Existing Surface	Recommendations	Adhesive / Thin-set	
Gypsum Board	Yes	Wallpaper	Remover wallpaper	Adhesive / Thin-set	Mapei Type 1/ Mapei Ultramastic ECO (or comparable products from other brands)
Plywood	Yes	Paint	Remove the paint or add a cement layer for stronger bonding		
Reinforcement of cement board fiber	Yes			Stone (Marble, Terrazzo, etc.)	Install on top of the existing finish
Concrete + mortar base	Yes	Extrusion cement panel / ALC panel	Yes		

### ■ Appearance of Joints



**Note:** There are spaces between the tiles of ECO-CART, which makes the back net and striped arks visible.

<https://www.inaxecocar.com/products/roughsawn/>


# FOR BETTER FUNCTION

## Sufficient ventilation is required



Proper ventilation is recommended for more effective ECOCARAT performance and to help control humidity.

### Ventilate frequently for 1 to 2 weeks after installation




The moisture of the adhesive may be present in the room and room temperature may increase.

### Avoid contact with fabric




The uneven surface of Ecocarot Plus tiles may damage fabric.

### Avoid sharp objects



The tile surface may be scratched or scraped.

### Do not use hooks, screws or hammers



Doing so can cause cracks and breakage. Please consult contractor.


# DAILY CARE

Dust regularly with a clean cloth. Avoid washing with water directly.




- Use of mild household detergent will enhance cleaning results
- Remove stains using melamine foam cleaning sponge
- For best results, use melamine foam sponge and mild detergent


Urine Stains




Restroom Grime




Toothpaste




Shoe Prints




Scuff Marks



Fingerprints





Coffee Stains



Food Spills



Nicotine Stains



### Cleaning Recommendation

For best results we suggest the use of a melamine foam sponge for the treatment of dirt and stains shown.


Detergents containing bleach: Read precautions before use.

General household cleaners refer to mild, non-abrasive agents used to clean furniture, wall paper, windows, electronics, etc. and can be used to clean tiles. Do not use thinners or cleansers with acids. Doing so will damage the surface and characteristics of the tile.



Hard to remove stains must be treated promptly for best results.

Lipstick



Hair Dye Liquid



### Other:

- Paint tool
- Pen (water based, oil based)
- Crayon
- Nail polish
- Ink

### Removal of Tough Stains

- Please be careful for dirt and detergent to turn to neither the side nor the back at the time of cleaning. Please use a line stick etc. if needed.
- Remove dirt and spills promptly as set-in stains may be difficult to remove by the methods noted above.
- To remove tough stains, use mild detergent on a toothbrush and gently work into the stain. Stain may be permanent if allowed to absorb over time.
- Regular care and inspection is recommended to maintain the beauty of the tile.

Cleaning tools that can NOT be used

#In case where dirt and a crack become severe.

Dirty dustcloth



Sand Eraser



Abrasive Sponge



Steel Wool Pad

