

BREATHING WALL-ECO CARAT

Rooted in traditional Japanese mud-wall construction, ECO CARAT is a sublime collection of interior wall tiles that combine natural materials and colors with exquisite patterns to impart a sense of unparalleled beauty and relaxation. Defined by design and technology excellence, ECO CARAT features moisture-regulating and odor reducing properties to help enhance indoor comfort.

VELE

Rounded convex squares form a simple pattern, rich in texture, light, and shadows.




APPLICATIONS (Interior Dry Wall ONLY)								
LIVING ROOM WALL	BEDROOM WALL	ENTRANCE WALL	HALLWAY WALL	RESTROOM	EXTERIOR WALL	BATH/SHOWER WALL	FLOOR	KITCHEN BACK
Yes	Yes	Yes	Yes	Yes ¹	No	No	No	No

¹. Above waste/water line


COLOR VARIATIONS*2			
V1	V2	V3	V4

*2. Please note: variations in color, shade, surface texture and size are natural characteristics of all our products and should be expected. Images shown are representative, but may not indicate all variations in these characteristics.


FIELD




ECP-30NET-WE1
White



ECP-30NET-WE2
Ivory



ECP-30NET-WE3
Beige




ECP-30NET-WE4
Grey

Material:	Porous ceramics/Glazed
Size/Piece:	30.3 x 30.3mm (1.19 x 1.19 in)
Size/Sheet:	303 x 303mm (11.93 x 11.93 in)
Thickness:	8.5mm
Joint:	Closed joint
Sq. Ft/Carton:	10.47
Sheets/Carton:	11
Mounting:	Back net-Paper
Weight/Carton:	27.6 lbs


TRIM/CORNERS

Dimension of sheet



ECP-30N-9014-WE1...WE4

Installation for corner
(External)



Material:	Porous ceramics/Glazed
Size/Piece:	(31.45+31.45)x30.3mm *(1.20+1.20)x1.19 in
Size/Sheet:	31.45+31.45)x303mm *(1.20+1.20)x11.93 in
Thickness:	5.5mm
Joint:	Closed joint
Ln. Ft/Carton:	3.86
Sheets/Carton:	4
Mounting:	NA (Loose piece)
Weight/Carton:	6.61 lbs

INSTALLATION

BASE MATERIAL SUITED		EXISTING WALL FINISHES		OTHER PRECAUTIONS	
Material:	Suitable	Existing Surface	Recommendations	Adhesive / Thin-set	
Gypsum Board	Yes	Wallpaper	Remove wallpaper	Adhesive / Thin-set	Mapei Type 1/ Mapei Ultramastic ECO (or comparable products from other brands)
Plywood	Yes	Paint	Remove the paint or add a cement layer for stronger bonding		
Reinforcement of cement board fiber	Yes				
Concrete + mortar base	Yes	Stone (Marble, Terrazzo, etc.)	Install on top of the existing finish	Grouting	Non-Grouting (Closed Joint)
Extrusion cement panel / ALC panel	Yes				

■ Installation Photo



Note: If possible, layout the tiles in a way that you do not have to cut the pieces.

<https://www.inaxecocarat.com/products/vele/>


FOR BETTER FUNCTION

Sufficient ventilation is required



Proper ventilation is recommended for more effective ECOCARAT performance and to help control humidity.

Ventilate frequently for 1 to 2 weeks after installation



The moisture of the adhesive may be present in the room and room temperature may increase.

Avoid contact with fabric




The uneven surface of Ecocarot Plus tiles may damage fabric.

Avoid sharp objects



The tile surface may be scratched or scraped.

Do not use hooks, screws or hammers



Doing so can cause cracks and breakage. Please consult contractor.


DAILY CARE

Dust regularly with a clean cloth. Avoid washing with water directly.



- Use of mild household detergent will enhance cleaning results
- Remove stains using melamine foam cleaning sponge
- For best results, use melamine foam sponge and mild detergent


Urine Stains




Restroom Grime




Toothpaste




Shoe Prints



Scuff Marks




Fingerprints





Coffee Stains



Food Spills



Nicotine Stains



Cleaning Recommendation

For best results we suggest the use of a melamine foam sponge for the treatment of dirt and stains shown.


Detergents containing bleach: Read precautions before use.

General household cleaners refer to mild, non-abrasive agents used to clean furniture, wall paper, windows, electronics, etc. and can be used to clean tiles. Do not use thinners or cleansers with acids. Doing so will damage the surface and characteristics of the tile.



Hard to remove stains must be treated promptly for best results.

Lipstick



Hair Dye Liquid



Other:

- Paint tool
- Pen (water based, oil based)
- Crayon
- Nail polish
- Ink

Removal of Tough Stains

- Please be careful for dirt and detergent to turn to neither the side nor the back at the time of cleaning. Please use a line stick etc. if needed.
- Remove dirt and spills promptly as set-in stains may be difficult to remove by the methods noted above.
- To remove tough stains, use mild detergent on a toothbrush and gently work into the stain. Stain may be permanent if allowed to absorb over time.
- Regular care and inspection is recommended to maintain the beauty of the tile.

Cleaning tools that can NOT be used

#In case where dirt and a crack become severe.

Dirty dustcloth



Sand Eraser



Abrasive Sponge



Steel Wool Pad

