


BREATHING WALL-ECOCARAT

Rooted in traditional Japanese mud-wall construction, ECOCARAT is a sublime collection of interior wall tiles that combine natural materials and colors with exquisite patterns to impart a sense of unparalleled beauty and relaxation. Defined by design and technology excellence, ECOCARAT features moisture-regulating and odor reducing properties to help enhane indoor comfort.



	APPLICATIONS (Interior Dry Wall ONLY)								
LIVING WA			RESTROOM	EXTERIOR WALL	BATH/ SHOWER WALL	FLOOR	KITCHEN BACK		
Ye	es	Yes	Yes	Yes	Yes*1	No	No	No	No

^{*1.} Above waste/water line



*2. Please note: variations in color, shade, surface texture and size are natural characteristics of all our products and should be expected. Images shown are representative, but may not indicate all variations in these characteristics.





FIELD



ECP-315-RAX1 White



ECP-315-RAX2 Beige



ECP-315-RAX3 Brown



ECP-315-RAX4 Dark Grey



ECP-315-RAX1A White (Relief A)



ECP-315-RAX2A Beige (Relief A)



ECP-315-RAX3A Brown (Relief A)



ECP-315-RAX4A Dark Grey (Relief A)

Material:	Porous ceramics/Glazed		
Size/Piece:	303 x 151.5mm (11.93 x 5.96 in)		
Size/Sheet:	NA (Loose piece)		
Thickness:	9mm (Relief A: 5.5mm)		
Joint:	Closed joint		
Sq. Ft/Carton:	10.47 (Relief A: 13.33)		
Sheets/Carton:	22 (Relief A: 28)		
Mounting:	NA (Loose piece)		
Weight/Carton:	25.4 lbs (Relief A: 25.4)		

TRIM/CORNERS

Short Edge Trim



Material:	Porous ceramics/Glazed		
Size/Piece:	303 x 151.5mm (11.93 x 5.96 in)		
Size/Sheet:	NA (Loose piece)		
Thickness:	5.5mm		
Joint:	Closed Joint		
Ln Ft/Carton:	13.5		
Sheets/Carton:	28		
Mounting:	NA (Loose piece)		
Weight/Carton:	25.4 lbs		





INSTALLATION

BASE MA	TERIAL SUITED	EXISTING '	WALL FINISHES	OTHER PRECAUTIONS		
Material:	Suitable	Existing Surface	Recommendations	Adhesive/ Thin-set	Mapei Type 1/ Mapei Ultramastic ECO (or comparable products from other brands)	
Gypsum Board	Yes	Wallpaper	Remover wallpaper			
Plymwood	Yes	Paint	Remove the paint or add a cement layer for stronger bonding	Trowels	3mm (½ in) * Wider trowel will lead to excess adhesive on	
Reinforcement of cement board fiber	Yes				the back.	
Concrete + mortar base	Yes	Stone (Marble, Terrazzo, etc.)	Install on top of the existing finish	Grouting	Non-Grouting (Closed Joint)	
Extrusion cement panel / ALC panel	Yes					

■ Application Pattern



There is a direction in this product. As shown in the figure above, the narrow relief is on the top, and the color number symbol on the back is on the bottom.

1	1	1	<u> </u>
1		1	↓ ·
1		1	<u> </u>
1		1	↓ ·
1	1	1	↓

When installing a 303x151 relief (relief), as shown in the figure above, please construct so that the upward row and the downward row are alternately arranged.

■ Installation Photo



https://www.inaxecocarat.com/products/granas-raxa/






FOR BETTER FUNCTION

Sufficient ventilation is required



Proper ventilation is recommended for more effective ECOCARAT performance and to help control humidity.

Ventilate frequently for 1 to 2 weeks after installation



The moisture of the the adhesive may be present in the room and room temperature may increase.

Avoid contact with fabric



The uneven surface of Ecocarat Plus tiles may damage fabric.

Avoid sharp objects



The tile surface may be scratched or scraped.

Do not use hooks, screws or hammers



Doing so can cause cracks and breakage. Please consult contractor.





DAILY CARE

Dust regularly with a clean cloth. Avoid washing with water directly.



- Use of mild household detergent will enhance cleaning results
- Remove stains using melamine foam cleaning sponge
- For best results, use melamine foam sponge and mild detergent

Urine Stains







Shoe Prints



Scuff Marks



Fingerprints



Food Spills





Nicotine Stains





Cleaning Recommendation

For best results we suggest the use of a melamine foam sponge for the treatment of dirt and stains shown.

Detergents containing bleach: Read precautions before use.

General household cleaners refer to mild, non-abrasive agents used to clean furniture, wall paper, windows, electronics, etc, and can be used to clean tiles. Do not use thinners or cleansers with acids. Doing so will damage the surface and characteristics of the tile.



Hard to remove stains must be treated promptly for best results.

Lipstick



Hair Dye Liquid



Other:

- Paint tool
- -Pen (water based, oil based)
- -Crayon
- -Nail polish

Removal of Tough Stains

- Please be careful for dirt and detergent to turn to neither the side nor the back at the time of cleaning. Please use a line stick etc. if needed.
- Remove dirt and spills promptly as set-in stains may be difficult to remove by the methods noted above.
- To remove tough stains, use mild detergent on a toothbrush and gently work into the stain. Stain may be permanent if allowed to absorb over time.
- Regular care and inspection is recommended to maintain the beauty of the tile.

Cleaning tools that can NOT be used

Dirty dustcloth



Sand Eraser



Abrasive Sponge



Steel Wool Pad



