

**Tubular Handle Set**



New York (NY Tubular Series)



Manhattan (MH Tubular Series)

**Application**

For residential entry, multi-family unit entry.

**Material**

Stainless Steel Levers and Escutcheons

**Finish**




- Satin Stainless Steel US32D/630
- Bright Polished Stainless Steel US32/629
- Two-tone Stainless Steel (Inside Lever Only) SP (Satin on lever grip, Polish on lever neck, inside plate, outside plate and handgrip.)
- Oil Rubbed Bronze on Stainless Steel 10B/613

\*See page 3 for finish availability.

**Specification**


- Door Thickness: 1-3/4" (44mm) standard  
Thick Door Kits available
- Backset: 2-3/8" (60mm) standard  
2-3/4" (70mm) optional
- Hanging: Hanging specification required.  
Latchbolt is field reversible.
- Center Distance: Lever to Cylinder 5-1/2" (140mm)
- Cylinder & Keys: 5-pin Schlage C keyway with 2 keys.
- Leverset Thru-bolts: 2 EA M4x35mm
- Deadbolt Thru-bolts: 2 EA M5x50mm

**Functions**



**Entrance (C563/C573)**


Deadbolt is locked or unlocked by key or thumb-turn inside.  
Thumb-piece from outside or lever from inside retract latchbolt.  
Deadbolt and latch are not interconnected.



**Entry Dummy (TDP)**

NY/ MH trim with rim dummy cylinder outside, dummy plate escutcheons inside.

**Door Preparation**



Please go to:  
<http://www.unisonhardware.com/Technical-Info> for the latest door preparation templates and installation instructions.