

Technical Specifications

Projecta™ 6036 Drop-In Whirlpool Bathtub

Letter	Description	R1D6036W
-	Drain Location	Universal end drain
-	Whirlpool Pump Location	Opposite end of drain
-	Cutout	58.00" x 34.00" (1473 mm x 864 mm)
-	Total Weight	769 lbs (349 kg)
-	Floor Loading	51.3 lb/ft² (250 kg/m²)
-	Operating Gallons (Min/Max)	45 gal (170L) / 54 gal (204 L)
-	Product Weight	68 lbs (31 kg)
L	Outer Length	60.00" (1524 mm)
W	Outer Width	36.00" (914 mm)
Н	Overall Height	21.00" (533 mm)
А	Overflow Height	17.50" (445 mm)
В	Short Edge to Drain Center	8.25" (210 mm)
С	Long Edge to Drain Center	18.00" (457 mm)
D	Drain Shoe Length	6.25" (159 mm)
Е	Deck Height	2.00" (51 mm)
F	Deck Width	3.75" (95 mm)
G	Service Access Dimensions	12.00" x 18.00" (305 mm x 457 mm)
Ι	Floor Cutout for Drain	12.00" x 4.00" (305 mm x 102 mm)
J	Interior Dimensions (bottom of bath) J(L) x J(W)	40.00" x 24.30" (1016 mm x 617 mm)

WHIRLPOOL 6036 MODEL

Each component requires a separate, dedicated GFCI protected circuit


Model with components	GFCI Outlet (60Hz)
Motor/Pump	120V 15A
Heater (if available)	120V 15A

Installed Left-Hand Orientation

- 4.75" **-**2.00" 9 J(L) f J(W) (G) Whirlpool Pump f w Overflow Heater F* 1 B → -(G - Optional)

*Deck width reflects only area indicated on detail.

Installed Right-Hand Orientation



NOTE: Drawings not to scale. Whirloool Pumr 10-jet system shown. A 6-jet system is also available in 6032 models only. End View

Drain/Overflow

©2019 Jacuzzi Luxury Bath • For additional information, call Customer Service 800-288-4002 • www.jacuzzi.com/baths Refer to installation instructions included with fixture before beginning installation. Please confirm product availability and specifications before commencing with any installation work.

KEY DIMENSIONS* [NOTE: The overall dimensions are nominal with a tolerance of +0 and -.25" (6mm).]

PRODUCT SPECIFICATIONS AND AVAILABILITY ARE SUBJECT TO CHANGE WITHOUT NOTICE

QC51000A