TECHNICAL SPECIFICATIONS

Luxura® 530 Whirlpool Bath with Integral Skirt

LXS6030 WLR 2XX Luxura 530 Whirlpool Bath with Integral Skirt

Left Hand (N790)

LXS6030 WRL 2XX Luxura 530 Whirlpool Bath with Integral

Skirt Right Hand (N795)

Luxura® 530 Bath with Integral Skirt

LXS6030 BLX XXX Luxura 530 Bath with Integral Skirt Left Hand

(EJ91)

LXS6030 BRX XXX Luxura 530 Bath with Integral Skirt Right Hand

(EJ96)



INSTALLATION NOTES

Refer to installation instructions included with fixture before beginning installation. Please confirm product availability and specifications before commencing with any installation work.

PRODUCT SPECIFICATIONS AND AVAILABILITY ARE SUBJECT TO CHANGE WITHOUT NOTICE.

KEY DIMENSIONS

DIMENSIONS

60" L x 30" W x 20-1/4" H

(1524 mm) L x (762 mm) W x (483 mm) H

DRAIN/OVERFLOW

A: 16-3/4" (425 mm) B: 9-1/4" (235 mm)

CUTOUT

Not Applicable

TOTAL WEIGHT

662 lb (300 kg) / 53 lb/ft² (258 kg/m²)

OPERATING GALLONAGE

N790, N795: 38 U.S. Gal. (144 Liters)

Max: 47 U.S. Gal. (178 Liters)

EJ91, EJ96: 40 U.S. Gal. (151 liters) Max: 47 U.S. Gal. (178 Liters)

PRODUCT WEIGHT

PRODUCT WEIGHT

N790, N795: 95 lb (43 kg)

EJ91, EJ96: 70 lb (32 kg) SKIRT MOUNTING

Integral

ELECTRICAL SPECIFICATIONS MODELS N790, N795 ONLY

Requires a dedicated GFCI protected separate circuit.

Motor/Pump: 120 VAC, 15 AMP, 60 Hz. RapidHeat™: 120 VAC, 15 AMP, 60 Hz.

HEATER (OPTIONAL) MODELS N790, N795 ONLY

Requires a dedicated GFCI protected separate circuit.

RapidHeat™: P/N S75000

Product Shown: Luxura 5 Whirlpool Bath with Integral Skirt Left Hand Model: N790

* Measurements inside unit represent cutout in floor to allow for drain/overflow.

FEATURES, UPGRADES & ACCESSORIES

- Right and Left Hand Drain Location
- Accessories / Hardware:

Trip-Lever Drain Kit #X559 Rotary Drain Kit, 26" Cable #8730 TheraPro Jet Ring Trim Kit: #GU44

AccuPro Jet Trim Kit: #GU44

• Trim Kit Finishes Available:

(827) - Chrome

(826) - Brushed Nickel

(849) - Oil Rubbed Bronze





