

TECHNICAL SPECIFICATIONS



Nova™ 6 Whirlpool Bath

NOV7242 WLR 2XX Nova 6 Whirlpool Bath Left Hand (6800)
 NOV7242 WRL 2XX Nova 6 Whirlpool Bath Right Hand (9235)
 NOV7242 WLB 2XX Nova 6 Whirlpool Bath Left Hand, Right Back Pump (DA70)

Nova™ 6 Bath

NOV7242 BUX XXX Nova 6 Bath (7263)

INSTALLATION NOTES

Refer to installation instructions included with fixture before beginning installation. Please confirm product availability and specifications before commencing with any installation work.

PRODUCT SPECIFICATIONS AND AVAILABILITY ARE SUBJECT TO CHANGE WITHOUT NOTICE.

KEY DIMENSIONS

DIMENSIONS

72" L x 42" W x 20-1/2" H
 (1829 mm) L x (1067 mm) W x (521 mm) H

DRAIN/OVERFLOW

A: 14-3/4" (375 mm) B: 8-1/2" (216 mm)

CUTOUT

70" x 40"

TOTAL WEIGHT

6800, 9235, DA70: 876 lb (397 kg) / 42 lb/sq. ft. (204 kg/m²)

7263: 847 lb (384 kg) 40 lb/ / sq. ft. (197 kg/m²)

OPERATING GALLONAGE

62 U.S. Gal. (235 Liters)

Max. 77 U.S. Gal. (291 Liters)

PRODUCT WEIGHT

6800, 9235, DA70: 110 lb (50 kg)

7263: 81 lb (37 kg)

SKIRT MOUNTING

Optional, U-Frame: #F958

ELECTRICAL SPECIFICATIONS MODELS 6800, 9235, DA70 ONLY

Requires a dedicated GFCI protected separate circuit.

Motor/Pump: 120 VAC, 15 AMP, 60 Hz.

RapidHeat™: 120 VAC, 15 AMP, 60 Hz.

HEATER (OPTIONAL MODELS 6800, 9235, DA70 ONLY)

Requires a dedicated GFCI protected separate circuit.

Product Shown: Nova 6 Whirlpool Bath Left Hand Model: 6800

* Measurements inside unit represent cutout in floor to allow for drain/overflow.

FEATURES, UPGRADES & ACCESSORIES

- Left or Right Hand Drain Location
- Accessories / Hardware:
 - Trip-Lever Drain Kit #X559
 - Rotary Drain Kit, 26" Cable #8730
 - TheraPro Jet Trim Kit: #GU44
 - AccuPro Jet Trim Kit: #GU45 (2 kits required)
- Trim Kit Finishes Available:
 - (827) – Chrome
 - (826) – Brushed Nickel
 - (849) – Oil Rubbed Bronze

