

TECHNICAL SPECIFICATIONS



Nova™ 536 Whirlpool Bath with Integral Skirt

NVS6036 WRL 2XX	Nova 536 Whirlpool Bath with Integral Skirt Right Hand (H529)
NVS6036 WLR 2XX	Nova 536 Whirlpool Bath with Integral Skirt Left Hand (H528)

Nova™ 536 Bath with Integral Skirt

NVS6036 BRX XXX	Nova 536 Bath with Integral Skirt Right Hand (H583)
NVS6036 BLX XXX	Nova 536 Bath with Integral Skirt Left Hand (H530)

INSTALLATION NOTES

Refer to installation instructions included with fixture before beginning installation. Please confirm product availability and specifications before commencing with any installation work.

PRODUCT SPECIFICATIONS AND AVAILABILITY ARE SUBJECT TO CHANGE WITHOUT NOTICE.

KEY DIMENSIONS

DIMENSIONS

60" L x 36" W x 19-1/4" H

(1524 mm) L x (914 mm) W x (489 mm) H

DRAIN/OVERFLOW

A: 14-5/8" (372 mm) B: 9" (229 mm)

CUTOUT

Not Applicable

TOTAL WEIGHT

H528, H529: 698 lb (317 kg) / 47 lb/sq. ft. (227 kg/m²)

H530, H583: 675 lb (306 kg) / 45 lb/sq. ft. (220 kg/m²)

OPERATING GALLONAGE

42 U.S. Gal. (159 Liters)

PRODUCT WEIGHT

H528, H529: 98 lb (45 kg)

H530, H583: 75 lb (34 kg)

SKIRT MOUNTING

Integral

ELECTRICAL SPECIFICATIONS MODELS H528, H529 ONLY

Requires a dedicated GFCI protected separate circuit.

Motor/Pump: 120 VAC, 15 AMP, 60 Hz.

RapidHeat™: 120 VAC, 15 AMP, 60 Hz.

HEATER (OPTIONAL MODELS H528, H529 ONLY)

Requires a dedicated GFCI protected separate circuit.

RapidHeat™: P/N S750000

Product Shown: Nova 536 Whirlpool Bath with Integral Skirt Left

Hand Model: H528

* Measurements inside unit represent cutout in floor to allow for drain/overflow.

FEATURES, UPGRADES & ACCESSORIES

- Right and Left Hand Drain Location
- Accessories / Hardware:
 - Trip-Lever Drain Kit #X559
 - Rotary Drain Kit, 26" Cable #8730
 - TheraPro™ Jet Rings Kit: #D095
 - AccuPro™ Jet Rings Kit: #P556
- Trim Kit Finishes Available:
 - (827) – Chrome
 - (826) – Brushed Nickel
 - (849) – Oil Rubbed Bronze

