



QAS144 • RYAN

LOW VOLTAGE MONORAIL
QUICK ADAPT SPOTS

Type	
Project	
Catalog No.	



CATALOG INFORMATION

MODEL	LAMP	MAX WATT	STEM LENGTH	DIMENSIONS	FINISH
QAS 144 RYAN	JC Bi-Pin 12V/24V	20W	X6 – 6"	1"Ø x 9-3/4"L	CH – Chrome SN – Satin Nickel

Ordering Instructions

MODEL	LENGTH	-	SOCKET
QAS 144		-	

Example: QAS144X6-CH

DESCRIPTION

- Extended mini tube with Dichroic glass shade.
- Quick Adapt Spot includes a Quick Adapt Jack, and Halogen JC Bi-Pin 12V 20W lamp.
- May be used with Jesco Monorail Systems, Standard Track Systems, or with Monopoint/Multipoint Systems – See COMPATIBLE SYSTEMS.

LAMPING:

JC Bi-Pin 12V 20W included.
Optional: 24V lamp, requires appropriate power supply (not supplied).

AIMING:

90° vertical and 360° rotation.

LISTING:

ETL Listed.

COMPATIBLE SYSTEMS



MONORAIL SYSTEM

The Monorail Fixture Adapter MA-FA (sold separately) provides the connection between the Quick Adapt Spot to the Monorail.



STANDARD TRACK SYSTEM

The Standard Track Adapter MA-TA-H (sold separately) enables the use of Quick Adapt Spots in Standard, Line Voltage H-Track Systems. Includes a 50W electronic transformer. Dimmable with an electronic or standard incandescent dimmer.



MONOPOINT / MULTIPOINT SYSTEM

Quick Adapt Spots may be directly mounted onto Monopoint or Multipoint canopies, which have built-in or remote transformer options.