



LV3000ICA

RECESSED LIGHTING
3" NEW CONSTRUCTION LOW VOLTAGE
AIRTIGHT

Type	
Project	
Catalog No.	



ORDERING INSTRUCTIONS

MODEL: LV3000ICA

DESCRIPTION

- 3" New Construction IC Airtight Low Voltage Housing
- Thermally protected, listed for damp locations
- UL listed for feed-through branch circuit wiring.
- Integral 120VAC 60Hz/12V magnetic transformers.
- Dimmable with magnetic low-voltage dimmers.
- Airtight IC units may be covered with insulation to conserve energy. Gasketed to prevent airflow through the housing from heating or cooling systems. Compliant with State of Washington restricted airflow requirements (WSEC Code)
- Dimensions: 10-7/8"W x 17-1/4"L x 7-1/2"H
- Cut-Out: 3-1/4"Ø

LAMP:
12V MR16 35W Max. Sold separately.

OTHER OPTIONS



LV3000R
Remodel Non-IC Low Voltage Housing
12V MR16 50W Max.
Dimensions: 3-1/2"W x 14-1/2"L x 4"D
Cutout: 3-1/4"Ø



LV3000B
New Construction Non-IC Low Voltage Housing
12V MR16 50W Max.
Dimensions: 6-1/4"W x 16-1/4"L x 4"D
Hanger Bars: up to 24"
Cutout: 3-1/4"Ø