


Туре	
Project	
Catalog No.	





COMPATIBLE TRIMS

GENERAL ILLUMINATION				ACCENT		WALL WASH	WET LOCATIONS	
Baffle	Reflector	Slot	Glass	Gimbal	Eyeball			
TM301	TM302	TM303	TM320	TM308	TM306	TM304	TM309*	TM315*

Complete Fixture consists of Housing and Trim. Order separately. See trim specification sheet for details. * 35W max.

DESCRIPTION

3" aperture low voltage recessed housing for general illumination. accent, wall wash and wet location. Designed for use in noninsulated ceiling or insulated ceiling where insulation are kept at a minimum distance of 3" from all sides.

HOUSING:

White-painted galvanized steel. 4-7/8" height allows for use in 2" x 6" joist. Adjustable for ceiling thickness up to 1-1/4".

JUNCTION BOX

UL Listed for a maximum of 8 12AWG through branch circuit conductors suitable for 90°C. (5) 1/2" knockouts with pry-out slots and (4) knockouts with integral cable clamps for attachment of nonmetallic Romex cable.

MOUNTING FRAME

Galvanized steel. 8-1/16"L x 5-1/4"W

HANGER BARS

Tooless adjustable from 12" to 24". Integral nails and T-bar clips.

Ceramic socket with aluminum heat shield for Bi Pin MR16 lamp.

TRANSFORMER

Magnetic 120V primary to 12V secondary 50W max. Access above ceiling required.

THERMAL PROTECTOR

Thermal protection device safe guard against overheating and improper installation.

DIMMING

Use only dimmers specifically designed for use with magnetic low voltage transformers. May be advertised as MLV, standard phase control or leading edge. May produce audible sound when used with dimmer.

LABELS

UL and cUL Listed to UL and CSA standards for non-IC applications in damp locations.

