




RLR-4110-xx

4" LED RETROFIT MODULE
LED RECESSED DOWNLIGHTS

Type	
Project	
Catalog No.	



DESCRIPTION

Easily convert any 4" incandescent recessed downlight to the latest in LED technology without special tools or rewiring. Incorporating Jesco's exclusive Driverless AC LED technology and patent pending inrush current protection the high lumen 10W COB produces 40% more lumen output than a 50W PAR20 or MR16. Our LED retrofit module operates directly from an AC sources eliminating the need an additional driver The unit is provided with a detachable E26 Base adapter that attaches into an existing E26 incandescent or optional GU24 socket. These lights are suitable for use in either IC/airtight or non-IC applications and in wet, damp or dry environments.

Designed for use with all of JESCO's 4" housings, also ETL classified for most competitor housings currently on the market they can be dimmed by most standard incandescent, electronic or magnetic low voltage and CFL/LED dimmers.

Without the need for the traditional LED driver you can expect years of reliable and energy saving service

FEATURES

- 770 lm from 10W
- High CRI of 80+
- Available in 2700K, 3000K and 4000K
- Advanced heat sink provides superior thermal management for 50,000 hours of operation with 70% lumen maintenance
- Patent pending inrush current protection
- Unique impact resistant polycarbonate lens provides uniform light output with lamp-like appearance
- Dimmable 10-100% with most leading or trailing edge incandescent or low voltage dimmers
- Securely mounts into housing.
- Integrated die cast aluminum trim and heat sink
- Optional GU24 connector cable for fluorescent housings

SPECIFICATIONS

Model	RLR-4110-XX-WH/WH
Description	LED Retrofit Module
Input Voltage	120 VAC 50/60Hz
Wattage	10W
CCT	2700K / 3000K / 4000K
Lumens*	770 lm
Efficacy	77 lm/W
CRI	80+
Dimmable**	10-100%: Triac, ELV, MLV, CFL/LED
Beam Angle	100°
Lamp Life	50,000 hours
Dimensions	4-15/16"Ø x 2 1/8"H
Environment	Wet, Dry, Damp
Certifications	ETL Listed, ETL certified,
Warranty	5 Years – see published warranty terms for detailed information.

* Based on 3000K

** Recommended - 45 fixtures maximum run on one 600W dimmer
- 23 fixtures maximum run on one 300W dimmer



ORDERING INFORMATION - 4" LED MODULE

MODEL	-	SIZE	-	WATTAGE	-	CCT	-	TRIM Finish
RLR	-	41	-	10	-		-	
		41 – 4 inch		10 – 10 Wattage		27- 2700K 30- 3000K 40- 4000K		WH/WH – White Baffle/White Trim



www.jescolighting.com
support@jescolighting.com
Tech Support: 855.592.0029

6625 Traffic Ave
Glendale, NY 11385
Main Line: 800.527.7796
Fax Line: 855.592.0029

219 South 6th Ave
City of Industry, CA 91746
Main Line: 626.333.3661
Fax Line: 626.333.2955

Rev 2
7/30/2015

Specifications subject to change without notice.





RLR-4110-xx

4" LED RETROFIT MODULE
LED RECESSED DOWNLIGHTS

Type	
Project	
Catalog No.	

Example: RLR-4110-27-WH/WH

COMPATIBLE JESCO LINE VOLTAGE HOUSINGS

MODEL	DESCRIPTION	
RS2000B, RS2000BA, RS2000IC, RS2000ICA	4" Line Voltage New Construction	
RS2000R, RS2000RA	4" Line Voltage Remodel	


OTHER COMPATIBLE LINE VOLTAGE HOUSINGS

HALO H99T, H99RT, H99ICT
ALL-PRO ET400, ET400R, ET400AT
JUNO TC1, TC1R,
CAPRI R4, RR4, R4ASIC
LITHONIA L3, L3R
THOMAS PS4, PS4RM, PS4ASIC

COMPATIBLE DIMMERS

MANUFACTURER	STYLE	MODEL NUMBER	TYPE
Lutron	Diva	DVCL-153P	(CFL/LED)
	Diva	DVELV-303P	(Electronic Low Voltage)
	Diva	DVLV-600P	(Magnetic Low Voltage)
	Maestro	MACL-153M	(CFL/LED)
	Maestro	MFR2-6DN-120	(Spec Grade)
	Skylark	SELV-300P	(Electronic Low Voltage)
	Skylark	S-600	(Incandescent)
Leviton	Skylark Contour	CTCL-153P	(CFL/LED)
	Acenti	Ate06-1LW	(Electronic Low Voltage)
Cooper	Trimatron	705	(Incandescent)
	Devine	D106P	(Incandescent/Magnetic/Low Voltage)
Pass & Seymour	Harmony		(Incandescent 600W)

ACCESSORIES



AC-GU24/CONN
Optional GU24 Socket Adaptor