



RS5500BICA

RECESSED LIGHTING
5" LINE VOLTAGE HOUSINGS

Type	
Project	
Catalog No.	



ORDERING INSTRUCTIONS

MODEL: RS5500BICA

DESCRIPTION

- 5" New Construction IC Airtight Line Voltage Housing
- Thermally protected, listed for damp locations.
- UL listed for feed-through branch circuit wiring.
- Dimmable with incandescent dimmers.
- J-box accessible through ceiling cut-out.
- IC Airtight units may be covered with insulation to conserve energy, and are Gasketed to prevent airflow through the housing from heating or cooling systems. Compliant with State of Washington restricted airflow requirements (WSEC Code).
- Dimensions: 7-1/2"W x 13-1/8"L x 7-3/8"H
- Hanger Bars: adjustable up to 24"
- Cut-Out: 5-1/2"Ø

LAMPS:

120V PAR20, PAR30, R20, R30, A19 50W Max. Sold separately.

OTHER OPTIONS



RS5500BA

New Construction Non-IC Airtight Line Voltage Housing
120V PAR20, PAR30, R20, R30, A19
75W Max.

Dimensions: 7-1/2"W x 13-1/8"L x 7-3/8"H
Hanger Bars: adj. Up to 24"
Cutout: 5-1/2"Ø



RS5500R

Remodel Non-IC Line Voltage Housing
120V PAR20, PAR30, R20, R30, A19
75W Max.

Dimensions: 6-1/8"W x 13-1/2"L x 7-1/4"H
Cutout: 5-1/2"Ø



RS5500RICA

Remodel IC Airtight Line Voltage Housing
120V PAR20, PAR30, R20, R30, A19
50W Max.

Dimensions: 6-1/8"W x 13-1/2"L x 7-1/4"H
Cutout: 5-1/2"Ø