




# RS6000RICA

RECESSED LIGHTING  
6" LINE VOLTAGE HOUSINGS

Type	
Project	
Catalog No.	



## ORDERING INSTRUCTIONS

**MODEL:** RS6000RICA

### DESCRIPTION

- 6" Line Voltage Remodel IC Airtight Housing
- Thermally protected, listed for damp locations.
- UL listed for feed-through branch circuit wiring.
- Dimmable with standard line-voltage incandescent dimmers.
- Remodeling housing models allow wiring below ceiling plane.
- J-box accessible through ceiling cut-out.
- Adjustable socket plate assures proper placement of different lamps.
- Airtight models are Gasketed to prevent airflow through the housing from heating or cooling systems. Compliant with State of Washington restricted airflow requirements (WSEC Code).
- IC units may be covered with insulation to conserve energy.
- Dimensions: 6-7/8"W x 13-1/2"L x 7-3/4"D
- Cut-Out: 6-1/2"Ø

**LAMPS:**  
 PAR16, PAR30, R30 120V 75W Max.  
 PAR38, R40 120V 100W Max.  
 A19 120V 40W Max.  
 Sold separately.

**WIRING:**  
 Housing is supplied with thermal protector

### OTHER OPTIONS



**RS6000R**  
 Non-IC Housing for Remodel  
 PAR16/30/38,R30/40,A19 120V 150W  
**Dimensions:** 6-7/8"W x 13-1/2"L x 7-3/4"D  
**Cutout:** 6-1/2"Ø



**RS6000RA**  
 Non-IC Airtight Housing for Remodel  
 PAR16/30/38,R30/40,A19 120V 150W  
**Dimensions:** 6-7/8"W x 13-1/2"L x 7-3/4"D  
**Cutout:** 6-1/2"Ø



**RS6000RIC**  
 IC Housing for Remodel  
 PAR30/R30 120V 75W  
 PAR38 120V 100W  
 A19 120V 40W  
**Dimensions:** 6-7/8"W x 13-1/2"L x 7-3/4"D  
**Cutout:** 6-1/2"Ø



**RS6000SR**  
 Non-IC Shallow Housing for Remodel  
 PAR30/R30 120V 75W  
 R40 120V 150W  
 PAR38 120V 100W  
 A19 120V 60W  
**Dimensions:** 7"W x 12"L x 5-1/2"D  
**Cutout:** 6-5/8"Ø




## RS6000RICA

RECESSED LIGHTING  
6" LINE VOLTAGE HOUSINGS

Type	
Project	
Catalog No.	

### OTHER OPTIONS



**RS6000B**  
Non-IC Universa Housing for New Construction  
PAR16/30/38,R30/40,A19 120V 150W  
**Dimensions:** 7"W x 10-1/4"L x 7-5/8"D  
**Hanger Bars:** adj. 14-1/2"~ 24-1/2"  
**Cutout:** 6-3/8"Ø




**RS6000BIC**  
IC Housing for New Construction  
PAR30/R30 120V 75W  
PAR38 120V 100W  
A19 120V 40W  
**Dimensions:** 7"W x 10-1/4"L x 7-5/8"D  
**Hanger Bars:** adj. 14-1/2"~ 24-1/2"  
**Cutout:** 6-3/8"Ø



**RS6000S**  
Non-IC Shallow Housing for New Construction  
PAR30/R30 120V 75W  
R40 120V 150W  
PAR38 120V 100W  
A19 120V 60W  
**Dimensions:** 7"W x 10-1/4"L x 5-1/2"D  
**Hanger Bars:** adj. 14-1/2"~ 24-1/2"  
**Cutout:** 6-3/8"Ø

### OTHER OPTIONS



**RS6000BA**  
Non-IC Airtight Universa Housing for New Construction  
PAR16/30/38,R30/40,A19 120V 150W  
**Dimensions:** 7"W x 10-1/4"L x 7-5/8"D  
**Hanger Bars:** adj. 14-1/2"~ 24-1/2"  
**Cutout:** 6-3/8"Ø



**RS6000BICA**  
IC Airtight Housing for New Construction  
PAR30/R30 120V 75W  
PAR38 120V 100W  
A19 120V 40W  
**Dimensions:** 7"W x 10-1/4"L x 7-5/8"D  
**Hanger Bars:** adj. 14-1/2"~ 24-1/2"  
**Cutout:** 6-3/8"Ø