



RS6000SR

RECESSED LIGHTING
6" LINE VOLTAGE HOUSINGS

Type	
Project	
Catalog No.	



ORDERING INSTRUCTIONS

MODEL: RS6000SR

DESCRIPTION

- 6" Line Voltage Remodel Non-IC Shallow Housing
- Thermally protected, listed for damp locations.
- UL listed for feed-through branch circuit wiring.
- Dimmable with standard line-voltage incandescent dimmers.
- Remodeling housing models allow wiring below ceiling plane.
- J-box accessible through ceiling cut-out.
- Adjustable socket plate assures proper placement of different lamps.
- Non-IC units require 3-inch of clearance on all sides.
- Shallow new construction and remodeling housings have a mere 5-1/2" depth.
- Dimensions: 7"W x 12"L x 5-1/2"D
- Cut-Out: 6-5/8"Ø

LAMPS:

PAR16, PAR30, R30 120V 75W Max.
 PAR38 120V 100W Max.
 R40 120V 150W Max.
 A19 120V 60W Max.
 Sold separately.

WIRING:

Housing is supplied with thermal protector.

OTHER OPTIONS



RS6000R
 Non-IC Housing for Remodel
 PAR16/30/38,R30/40,A19 120V 150W
Dimensions: 6-7/8"W x 13-1/2"L x 7-3/4"D
Cutout: 6-1/2"Ø



RS6000RA
 Non-IC Airtight Housing for Remodel
 PAR16/30/38,R30/40,A19 120V 150W
Dimensions: 6-7/8"W x 13-1/2"L x 7-3/4"D
Cutout: 6-1/2"Ø



RS6000RIC
 IC Housing for Remodel
 PAR30/R30 120V 75W
 PAR38 120V 100W
 A19 120V 40W
Dimensions: 6-7/8"W x 13-1/2"L x 7-3/4"D
Cutout: 6-1/2"Ø



RS6000RICA
 IC Airtight Housing for Remodel
 PAR30/R30 120V 75W
 PAR38 120V 100W
 A19 120V 40W
Dimensions: 6-7/8"W x 13-1/2"L x 7-3/4"D
Cutout: 6-1/2"Ø




RS6000SR

RECESSED LIGHTING
6" LINE VOLTAGE HOUSINGS

Type	
Project	
Catalog No.	

OTHER OPTIONS



RS6000B
Non-IC Universa Housing for New Construction
PAR16/30/38,R30/40,A19 120V 150W
Dimensions: 7"W x 10-1/4"L x 7-5/8"D
Hanger Bars: adj. 14-1/2"~ 24-1/2"
Cutout: 6-3/8"Ø




RS6000BIC
IC Housing for New Construction
PAR30/R30 120V 75W
PAR38 120V 100W
A19 120V 40W
Dimensions: 7"W x 10-1/4"L x 7-5/8"D
Hanger Bars: adj. 14-1/2"~ 24-1/2"
Cutout: 6-3/8"Ø



RS6000S
Non-IC Shallow Housing for New Construction
PAR30/R30 120V 75W
R40 120V 150W
PAR38 120V 100W
A19 120V 60W
Dimensions: 7"W x 10-1/4"L x 5-1/2"D
Hanger Bars: adj. 14-1/2"~ 24-1/2"
Cutout: 6-3/8"Ø

OTHER OPTIONS



RS6000BA
Non-IC Airtight Universa Housing for New Construction
PAR16/30/38,R30/40,A19 120V 150W
Dimensions: 7"W x 10-1/4"L x 7-5/8"D
Hanger Bars: adj. 14-1/2"~ 24-1/2"
Cutout: 6-3/8"Ø



RS6000BICA
IC Airtight Housing for New Construction
PAR30/R30 120V 75W
PAR38 120V 100W
A19 120V 40W
Dimensions: 7"W x 10-1/4"L x 7-5/8"D
Hanger Bars: adj. 14-1/2"~ 24-1/2"
Cutout: 6-3/8"Ø