

Туре	
Project	
Catalog No.	



SGA-LED: ADJUSTABLE LED SLEEK ULTRA

DESCRIPTION

SG-LED & SGA-LED are designed to replace existing fluorescent fixtures, it has a low profile design with minimal footprint. Environmentally friendly with no Mercury and no UV or IR emission. The LED Sleek Ultra, Fixed or Adjustable, may be interconnected end-to-end with Direct Connection (SG-DC) or with various connecting cables (SG-CCx). Fixture may be hardwired by using a Hardwire Box (SG-B or SG-BM) or plugged directly into standard wall outlet with a cord and 3 prong plug (sold separately). Each fixture includes (1) Direct Connector (SG-DC), and (2) Vertical Mounting Clips (SG-MC-V). The SG-LED also includes (2) 45° Angled Mounting Clips (SG-MC-45). The LED Sleek Ultra Adjustable features full 360 deg rotation and includes an ON/OFF switch. The LED Sleek Ultra Fixed features an optional ON/OFF switch.

SPECIFICATIONS

Voltage	120V		
CRI	80		
Max Run	80 linear feet		
Beam Angle	130°		
Operating Temp *	4°F to 104°F		
Lamp Life	50,000 hours		
Dimensione	SG-LED : 3/4" W x 1-3/8" H		
Dimensions	SGA-LED : 3/4" W x 1-5/8" H		
Housing	Aluminum		
Environment	Indoor - Dry 🛓		
Certifications	c-UL-us		
Warranty	5 Years – see published warranty terms for detailed information.		

^f Exceeding the operating temperature values may damage the LEDs by reducing the lifespan, lumen output, adversely impact color consistency, and void the warranty. It is recommended adequate airflow and heatsinking be taken into consideration in the installation and application of this product. Improper thermal management may lead to premature product failure.

LUMEN DATA

Part Number	Watts	Color Temp	Lumens	Efficacy (Im/W)		
	4.5	3000K	458	95		
SG-LED-12 SGA-LED-12		4000K	475	106		
OOA LED 12		6000K	485	108		
		3000K	866	111		
SG-LED-24 SGA-LED-24	7.8	4000K	896	115		
CONCEED 24		6000K	905	116		
	11.5	3000K	1335	116		
SG-LED-36 SGA-LED-36		4000K	1360	118		
00/1222 00		6000K	1390	121		
	15.2	3000K	1772	117		
SG-LED-48 SGA-LED-48		4000K	1863	123		
CONCEED 40		6000K	1875	123		
	19.5	3000K	2193	112		
SG-LED-60		4000K	2250	115		
		6000K	2358	121		


Note: Not dimmable.

For Indoor – Damp and Inside Closet/Cabinet applications add the prefit "E" (ex.- ESG-LED-xx)



www.jescolighting.com support@jescolighting.com Tech Support: 855.592.0029 15 Harbor Park Drive Port Washington, NY 11050 Main Line: 800.527.7796 Fax Line: 855.265.5768 219 South 6th Ave City of Industry, CA 91746 **Main Line:** 855.654.0110 **Fax Line:** 626.333.2955


Specifications subject to change without notice.



Example: SGA-LED-12-30-W-SW

Note: For Indoor - Damp and Inside Closet/Cabinet applications add the prefit "E" (ex.- ESG-LED-xx)

WIRING DIAGRAMS - For reference purposes only. Not for installation. Not to scale.



- A. SG-LED or SGA-LED (Fixture)
- B. SG-PCxx-W (Power Cord)
- C. SG-DC (Direct Connector)
- D. SG-CC-xx (Connecting Cable)
- E. SG-Bx (Optional Hard Wire Box)

219 South 6th Ave

City of Industry, CA 91746

Main Line: 855.654.0110

Fax Line: 626.333.2955

Specifications subject to change without notice.



SG-LED & SGA-LED

ACCESSORIES & COMPONENTS

COVE / CABINET / SHOWCASE / DISPLAY LED SLEEK ULTRA FIXED & ADJUSTABLE

Туре	
Project	
Catalog No.	

	Part Number	Description] [Part Number	Description
Contraction of the second seco	SG-PC24-W SG-PC72-W SG-PC96-W SG-PC144-W	Power Cord & Plug 2' white 6' white 8' white 12' white	fo	SG-CC6 SG-CC12 SG-CC24 SG-CC36	Connecting Cable 6" white 12" white 24" white 36" white
Jes:	SG-PCL SG-PCLL	Right Angle Power Cord & Plug 6" (From back) 6" (From front)		SG-CC6L SG-CC12L SG-CC24L SG-CC36L	Right Angle Connecting Cable 6" white 12" white 24" white 36" white
E C	SG-BM	Commercial Grade Metal Hard- Wire Box. Enables fixtures to be controlled by a wall switch. 2-3/4" L x 1-3/4" W x 1-3/4" H	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	SG-BM-SW	Commercial Grade Metal Hard-Wire Box with Switch. 3-1/2" L x 2" W x 1-1/8" H
	SG-MC-A	Mounting Clip Adjustable. Stainless Steel.	0	SG-B	Plastic Hard-Wire Box with Switch. 3-5/8" L x 2-1/2" W x 1-3/8" H
	SG-MC-V	Mounting Clip 0° vertical mount. Stainless Steel. (2) included with each fixture.		SG-MC-VH	Mounting Clip 90° vertical mount. Vertical and horizontal mount. Stainless Steel.
2.	SG-MC-45	Mounting Clip 45° vertical mount. Stainless Steel. (2) included only with SG-LED.			

Note: All accessories also function with JESCO's SG-4 & SG-5 fluorescent and S201 & S401 LED fixtures for easy retrofitting or interconnecting.



www.jescolighting.com support@jescolighting.com Tech Support: 855.592.0029 15 Harbor Park Drive Port Washington, NY 11050 **Main Line:** 800.527.7796 **Fax Line:** 855.265.5768 219 South 6th Ave City of Industry, CA 91746 **Main Line:** 855.654.0110 **Fax Line:** 626.333.2955

Specifications subject to change without notice.