



**TM201**

**RECESSED LIGHTING**  
4" APERTURE LINE VOLTAGE TRIMS

Type	
Project	
Catalog No.	



**CATALOG INFORMATION**

MODEL	BAFFLE / TRIM FINISH
TM201	ABAB – Antique Bronze / Antique Bronze
	BKBK – Black / Black
	BKST – Black / Satin Chrome
	BKWH – Black / White
	STST – Satin Chrome / Satin Chrome
	WHST – White / Satin Chrome
	WHWH – White / White

**Ordering Instructions**  
**Example:** MODEL – FINISH  
 TM201 – STST

**COMPATIBLE LINE VOLTAGE HOUSINGS**



**RS2000B**  
 Non-IC Universal Housing for New Construction  
 PAR16/20 120V 50W  
**Dimensions:** 5-1/4"W x 8"L x 5-1/2"D  
**Hanger Bars:** adj. 14-1/2"~ 24-1/2"  
**Cutout:** 4-3/8"Ø



**RS2000IC**  
 IC Housing for New Construction  
 PAR16/20 120V 50W  
**Dimensions:** 5-1/4"W x 8"L x 6"D  
**Hanger Bars:** adj. 14-1/2"~ 24-1/2"  
**Cutout:** 4-3/8"Ø



**RS2000R**  
 Non-IC Housing for Remodel  
 PAR16/20 120V 50W  
**Dimensions:** 4-5/8"W x 12"L x 5-1/2"D  
**Cutout:** 4-3/8"Ø

**DESCRIPTION**

- Recessed Lighting – Step Baffle 4" aperture Line Voltage trim.
- Use PAR16, PAR20 120V 50W Max.
- Ideal for use in ceilings, cabinets and displays.
- Dimensions: 3-3/8"A x 5"Ø
- Listings: UL and C-UL listed.

**COMPATIBLE LINE VOLTAGE HOUSINGS**



**RS2000BA**  
 Non-IC Airtight Universal Housing for New Construction  
 PAR16/20 120V 50W  
**Dimensions:** 5-1/4"W x 8"L x 5-1/2"D  
**Hanger Bars:** adj. 14-1/2"~ 24-1/2"  
**Cutout:** 4-3/8"Ø



**RS2000ICA**  
 IC Airtight Housing for New Construction  
 PAR16/20 120V 50W  
**Dimensions:** 5-1/4"W x 8"L x 6"D  
**Hanger Bars:** adj. 14-1/2"~ 24-1/2"  
**Cutout:** 4-3/8"Ø



**RS2000RA**  
 Non-IC Airtight Housing for Remodel  
 PAR16/20 120V 50W  
**Dimensions:** 4-5/8"W x 12"L x 5-1/2"D  
**Cutout:** 4-3/8"Ø