



TM210

RECESSED LIGHTING
4" APERTURE LINE VOLTAGE TRIMS

Type	
Project	
Catalog No.	



CATALOG INFORMATION	
MODEL	TRIM FINISH
TM210	WH - White

- | DESCRIPTION |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <ul style="list-style-type: none"> • Recessed Lighting – Dropped Showe Trim With Opal Glass 4" aperture Line Voltage trim. • Use PAR16, PAR20 120V 50W Max. • Ideal for use in ceilings, cabinets and displays. • Includes gasket for use in damp locations • Dimensions: 3-3/8"A x 5"Ø x 1"Ext • Listings: UL and C-UL listed. |

Ordering Instructions
Example:

MODEL	-	FINISH
TM210	-	WH

COMPATIBLE LINE VOLTAGE HOUSINGS



RS2000B
Non-IC Universal Housing for New Construction
PAR16/20 120V 50W
Dimensions: 5-1/4"W x 8"L x 5-1/2"D
Hanger Bars: adj. 14-1/2"~ 24-1/2"
Cutout: 4-3/8"Ø



RS2000IC
IC Housing for New Construction
PAR16/20 120V 50W
Dimensions: 5-1/4"W x 8"L x 6"D
Hanger Bars: adj. 14-1/2"~ 24-1/2"
Cutout: 4-3/8"Ø



RS2000R
Non-IC Housing for Remodel
PAR16/20 120V 50W
Dimensions: 4-5/8"W x 12"L x 5-1/2"D
Cutout: 4-3/8"Ø

COMPATIBLE LINE VOLTAGE HOUSINGS



RS2000BA
Non-IC Airtight Universal Housing for New Construction
PAR16/20 120V 50W
Dimensions: 5-1/4"W x 8"L x 5-1/2"D
Hanger Bars: adj. 14-1/2"~ 24-1/2"
Cutout: 4-3/8"Ø



RS2000ICA
IC Airtight Housing for New Construction
PAR16/20 120V 50W
Dimensions: 5-1/4"W x 8"L x 6"D
Hanger Bars: adj. 14-1/2"~ 24-1/2"
Cutout: 4-3/8"Ø



RS2000RA
Non-IC Airtight Housing for Remodel
PAR16/20 120V 50W
Dimensions: 4-5/8"W x 12"L x 5-1/2"D
Cutout: 4-3/8"Ø