

TM301

RECESSED DOWNLIGHTS

3" APERTURE TRIM • ADJUSTABLE STEP BAFFLE

Туре	
Project	
Catalog No.	



HOUSING	CEILING	MR16	GU10	
LV3000B	Non-IC	50W	_	
LV3000ICA	IC Airtight	35W	_	
LV3000R	Non-IC	50W	_	
RS3000B	Non-IC	_	50W	
RS3000ICA	IC Airtight	_	35W	
RS3000R	Non-IC	_	50W	

CATALOG INFORMATION

MODEL	FINISH		BAFFLE / TRIM
TM301	ABAB	_	Antique Bronze / Antique Bronze
	BKCH*	_	Black / Chrome
	BKWH	_	Black / White
	STST	_	Satin Chrome / Satin Chrome
	STWH*	_	Satin Chrome / White
	WHWH	_	White / White
	* While su	ipplie.	s last only.

Ordering Instructions Example:

MODEL TM301

FINISH

ABAB

COMPATIBLE LINE VOLTAGE HOUSINGS



RS3000B

New Construction Non-IC Housing 120V GU10 50W Max.

Dimensions: 5-1/4"W x 7-3/4"L x 4"D

Hanger Bars: up to 24" Cutout: 3-1/4"Ø



RS3000ICA

New Construction IC Airtight Housing

120V GU10 35W Max.

Dimensions: 7-1/2"W x 12-3/8"L x 7-1/4"[

Hanger Bars: up to 26" Cutout: 3-1/4"Ø



RS3000R

Remodel Non-IC Housing 120V GU10 50W Max.

Dimensions: 3-1/2"W x 11"L x 4"D

Cutout: 3-1/4"Ø

DESCRIPTION

- Adjustable Step Baffle 3" aperture line and low voltage trim.
- Ideal for use in ceilings, cabinets and displays.
- 35° adjustment from vertical
- Dimensions: 3"A x 3-5/8"Ø Listings: UL and C-UL listed.

COMPATIBLE LOW VOLTAGE HOUSINGS



LV3000B

New Construction Non-IC Housing 12V MR16 50W Max.

Dimensions: 6-1/4"W x 16-1/4"L x 4"D

Hanger Bars: up to 24" Cutout: 3-1/4"Ø



LV3000ICA

New Construction IC Airtight Housing

12V MR16 35W Max.

Dimensions: 10-7/8"W x 17-1/4"L x 7-1/2"D

Hanger Bars: up to 26"

Cutout: 3-1/4"Ø



LV3000R

Remodel Non-IC Housing 12V MR16 50W max

Dimensions: 3-1/2"W x 14-1/2"L x 4"D

Cutout: 3-1/4"Ø