



# TM308

**RECESSED LIGHTING**  
3" APERTURE LINE VOLTAGE TRIMS

Type	
Project	
Catalog No.	



HOUSING	CEILING	MR16	GU10
LV3000B	Non-IC	50W	–
LV3000ICA	IC Airtight	35W	–
LV3000R	Non-IC	50W	–
RS3000B	Non-IC	–	50W
RS3000ICA	IC Airtight	–	35W
RS3000R	Non-IC	–	50W

### CATALOG INFORMATION

MODEL	FINISH
TM308	AB – Antique Bronze
	BK – Black
	CH – Chrome
	ST – Satin Chrome
	WH – White

Ordering Instructions **MODEL** – **FINISH**  
 Example:  –

### DESCRIPTION

- Adjustable Gimbal Ring 3" aperture line and low voltage trim.
- Ideal for use in ceilings, cabinets and displays.
- 35° adjustment from vertical
- Dimensions: 3"A x 3-5/8"Ø x 1/2"Ext
- Listings: UL and C-UL listed.

### COMPATIBLE LINE VOLTAGE HOUSINGS



**RS3000B**  
 New Construction Non-IC Housing  
 120V GU10 50W Max.  
**Dimensions:** 5-1/4"W x 7-3/4"L x 4"D  
**Hanger Bars:** up to 24"  
**Cutout:** 3-1/4"Ø



**RS3000ICA**  
 New Construction IC Airtight Housing  
 120V GU10 35W Max.  
**Dimensions:** 7-1/2"W x 12-3/8"L x 7-1/4"D  
**Hanger Bars:** up to 26"  
**Cutout:** 3-1/4"Ø



**RS3000R**  
 Remodel Non-IC Housing  
 120V GU10 50W Max.  
**Dimensions:** 3-1/2"W x 11"L x 4"D  
**Cutout:** 3-1/4"Ø

### COMPATIBLE LOW VOLTAGE HOUSINGS



**LV3000B**  
 New Construction Non-IC Housing  
 12V MR16 50W Max.  
**Dimensions:** 6-1/4"W x 16-1/4"L x 4"D  
**Hanger Bars:** up to 24"  
**Cutout:** 3-1/4"Ø



**LV3000ICA**  
 New Construction IC Airtight Housing  
 12V MR16 35W Max.  
**Dimensions:** 10-7/8"W x 17-1/4"L x 7-1/2"D  
**Hanger Bars:** up to 26"  
**Cutout:** 3-1/4"Ø



**LV3000R**  
 Remodel Non-IC Housing  
 12V MR16 50W max  
**Dimensions:** 3-1/2"W x 14-1/2"L x 4"D  
**Cutout:** 3-1/4"Ø