

WARNING

WE RECOMMEND INSTALLATION OF THIS LIGHTING FIXTURE BE DONE BY A LICENSED ELECTRICIAN.
WARNING *** SWITCH OFF THE MAIN ELECTRICAL SUPPLY FROM THE MAIN FUSE BOX/CIRCUIT BREAKER BEFORE INSTALLATION.
INSPECT ITEM CAREFULLY BEFORE ATTEMPTING TO INSTALL. IF THERE IS ANY DAMAGE OR OBVIOUS DEFECT, DO NOT INSTALL. ITEM MAY NOT BE RETURNED ONCE IT HAS BEEN INSTALLED.

CARE AND MAINTENANCE

To clean the outside of the fixture, use a dry or slightly dampened clean cloth (use clean water, never a solvent) to wipe the surface of the fixture.










To clean the inside of the fixture, first disconnect power to the fixture by turning off the circuit breaker or by removing the fuse at the fuse box. Next, use a dry or slightly dampened clean cloth (use clean water, never a solvent) to wipe the interior surface of the fixture.

Do not use any cleaners with chemical, solvents or harsh abrasives. Use only a dry soft cloth to dust or wipe carefully.

NOTICE& IMPORTANT SAFETY INSTRUCTIONS


- * Please make sure that you have all parts indicated before you begin assembly of this item
- * This item should be assembled on a soft surface to prevent scratching the finish during assembly
- * To reduce the risk of fire, electrical shock or injury to persons or property, please follow the guideline below for safe use and installation
- *The external flexible cable or cord of this lamp cannot be replaced
If the cord is damaged, the lamp shall be destroyed

Part List and Hardware List

PIECE	DESCRIPTION	PICTURE	QUANTITY	PIECE	DESCRIPTION	PICTURE	QUANTITY
A	outlet box screw		2X	F	ground screw		1X
B	back plate		1X	G	socket ring		2X
C	lamp body		1X	H	shade		2X
D	mounting screw		3X	I	bulb		2X
E	wire connector		3X				

JONATHAN Y

Model#: JYL7482A / JYL7482B
Product Dimensions: 17.25"W x 9.25"E x 9.5"H




PREPARATION

Before beginning assembly of product, make sure all parts are present. Compare parts with package contents list and hardware contents list. If any part is missing or damaged, do not attempt to assemble the product.

Estimated Assembly Time: 20 minutes.

1. Fix the crossbar (B) to the junction box with outlet box screws (A).
2. Place the lamp body (C) on the crossbar (B) and lock it with mounting screws (D)
3. The lamp shade (H) is set into the body (C), and then use the socket ring (G) to lock.
4. Screw bulb (J) onto body (C)

Connect, Hot, Black or Red Outlet Supply Wire to:	Connect, Neutral, White Outlet Supply Wire to:
Black	White
* Parallel Cord (round & smooth)	* Parallel Cord (square & ridged)
Clear, Brown, Gold or Black without Tracer (colored stripes)	Clear, Brown, Gold or Black with Tracer (colored stripes)
Insulated Wire (not green) with copper metal conductor	Insulated Wire (not green) with Silver metal conductor.



*Note: When parallel wire (SPT I & SPT II) is used. The neutral wire is square shaped and ridged and the hot wire will be round in shape and smooth. (See Illustration on left.)

Grounding Instructions:

a) For installation in the United States: Wrap ground wire from outlet box around green ground screw(F) on mounting bracket, no less than 2" from wire end. Tighten ground screw(F). If fixture is supplied with a ground wire, connect to outlet ground wire with a wire connector.

b) For installation in Canada: If fixture is supplied with ground wire, wrap ground wire around green grounding screw on mounting bracket. Tighten ground screw.


5. Orient the back plate (B) so that the outlet box screw(A) protruding from the mounting bracket go into the holes in the back plate ,then secure it with the provided mounting screw(D).






6. Put metal ring(G) and the metal shade(H) over lamp body (C) and secure the metal shade(H) by socket ring(G).

7. Install bulbs(I). Be sure to use light bulb(I) with wattage no greater than specified on this fixture. Always make sure that electrical current is turned off before changing bulbs(I).





PLEASE USE TYPE "A" BULB MAX 40-WATT OR CFL BULB MAX 13-WATT OR LED BULB MAX 9-WATT, THERE ARE 2PCS LED BULB 9-WATT IN THE BOX.

ENJOY YOUR LAMP



PIECE	DESCRIPTION	PICTURE	QUANTITY	PIECE
A	outlet box screw		2X	F
B	crossbar		1X	G
C	body		1X	H
D	mounting screw		3X	I
E	wire connector		3X	

- 1 灯 $8''W \times 8.5''E$
 = 2 灯 $17.3''W \times 9.25''E$
 = 3 灯 $26.6''W \times 9.25''E$

DESCRIPTION	PICTURE	QUANTITY
ground screw		1X
socket ring		2X
shade		2X
bulb		2X

x 9.44" H

E x 9.44" H

E x 9.44" H