



Catalog Number
Notes
Type

Contractor Select™

**JSBC**

**JUNO SLIMBASICS™ LED SURFACE MOUNT DOWNLIGHT**



Sleek, low-profile LED round surface mount downlights in 5" and 7" sizes. Provides economical installation by mounting directly over standard junction boxes. Provides general illumination in residential and commercial applications including multi-family and hospitality. Ideal for use in corridors, foyers, living spaces, closets, hallways, pantries, stairways and much more. Packaging made from recyclable cardboard.

**FEATURES:**

- Installs into industry standard junction boxes
- Available in 3000K color temperature
- Minimum 90 CRI



Catalog Number	UPC	Description	Lumens	Input Watts	CCT	CRI	Voltage	Finish	Pallet qty.
JSBC 5IN 30K 90CRI WH M6	00193048340167	LED Surface Mount Downlight	650	11W	3000K	90	120V	White	1080
JSBC 7IN 30K 90CRI WH M6	00193048340389	LED Surface Mount Downlight	1050	17W	3000K	90	120V	White	750



## Specifications

### INTENDED USE:

Sleek, low-profile LED round surface mount downlights in 5" and 7" sizes • Provides economical installation by mounting directly over standard junction boxes • Provides general illumination in residential and commercial applications including multi-family and hospitality • Ideal for use in corridors, foyers, living spaces, closets, hallways, pantries, stairways and much more • Packaging made from recyclable cardboard

### CONSTRUCTION:

Shallow, 1" low profile with metal housing and white finish • Metal backplate allows for solid installation to junction box.

### ELECTRICAL:

Dedicated 120 volt (120) driver at 50/60Hz • Power factor > 0.9 at 120V input • 120 volt driver is dimmable with the use of most incandescent, magnetic low voltage and electronic low voltage wall box dimmers.

### JUNCTION BOX MOUNTING:

Fixture provided with leads for direct wire connection in j-box • Installs directly to industry standard junction boxes • Compatible boxes include 3" and 4" metal or plastic standard and fire rated round and octagon junction boxes • Compatible with pancake boxes if enough depth is allowed for connections and wiring space • Quick mount bracket provides easy twist turn locking of fully assembled fixture to junction box • Suitable for wall and ceiling mount • Suitable for use within closet storage spaces when installed per NEC requirements. Junction box sizes vary - Verify compatibility with fixture prior to installation

### LISTINGS:

ENERGY STAR® certified product. • Certified to the high efficacy requirements of California T24 JAB-2019 • CSA listed for US and Canada

### WARRANTY:

5-year limited warranty. Complete warranty terms located at:

[www.acuitybrands.com/support/warranty/terms-and-conditions](http://www.acuitybrands.com/support/warranty/terms-and-conditions)

**Note:** All reports are based on published industry procedures; actual performance may differ as a result of the end-user environment and applications.

All values are design or typical values, measured under laboratory conditions at 25 °C.

Specifications subject to change without notice.

## Dimensions

	Width	Depth
JSBC 5IN	5.25" (13.6)	1" (2.6)
JSBC 7IN	7.15" (18.2)	1" (2.6)

All dimensions are inches (centimeters) unless otherwise indicated.

