

KALLISTA®

One™ by KALLISTA Wall-mount single-control sink faucet P26613-00

Features

- High-quality solid-brass construction for durability and reliability
- Spout reach is 9-5/16" (237 mm)
- Includes soft-touch drain
- Wall-mount installation
- 1.2 gpm (4.5 lpm) maximum flow rate
- Valve sold separately

Required Products/Accessories

For wall-mount installation

P41299-00 Ceramic valve for wall-mount single-control sink faucet

Recommended Products/Accessories

P74234-WO Under-mount Sink, Soft Rectangle with Overflow, Glazed

P34401-00 Towel Bar, 24"

P34407-00 Disc Hook



ADA

CSA B651

OBC

Codes/Standards

ASME A112.18.1/CSA B125.1

NSF/ANSI/CAN 61

NSF/ANSI/CAN 372

DOE - Energy Policy Act 1992

EPA WaterSense®

California Energy Commission (CEC)

ADA

ICC/ANSI A117.1

CSA B651

OBC

KALLISTA® Five-Year Limited Warranty

See website for detailed warranty information.

Available Colors/Finishes

Color tiles intended for reference only.

Color	Code	Description
	CP	Polished Chrome
	BL	Matte Black
	ULB	Unlacquered Brass
	BAF	Brushed French Gold
	BN	Brushed Nickel
	SN	Polished Nickel
	2MB	Brushed Moderne Brass

1-888-4-KALLISTA (1-888-452-5547)


Kallista reserves the right to make revisions without notice to product specifications.

For the most current Specification Sheet, go to www.kallista.com.

11-14-2025 11:30 - US/CA

KALLISTA

One™ by KALLISTA
Wall-mount single-control sink faucet
P26613-00



Technical Information

All product dimensions are nominal.

Faucet flow rate: 1.2 gal/min (4.5 l/min)

Drain included: Yes

Drain with
overflow: Yes

Drain tailpiece
included: Yes

Spout:

Spout reach: 9-5/16" (236 mm)

Notes

Install this product according to the installation instructions.

ADA, OBC, CSA B651 compliant when installed to the specific requirements of these regulations.