



## Classic Wardrobe Lift

Pulling the handle of the Classic Wardrobe Lift moves the clothes rail out and down. The lift's movement is controlled by a self-regulating system that prevents the fitting from swivelling downwards uncontrolled. The unique interaction of the lift kinematics and control lever enables effortless lifting with a full load.

The Classic Wardrobe Lift is available in two widths: 445 - 1168 mm (17 ½ - 45 ⅞") for loads up to 12 kg (26.5 lbs) and 805 - 1168 mm (31 ¾ - 45 ⅞") for loads up to 15 kg. A **minimum load of 4 kg (9lbs)** is required for use. The width can be adjusted by 183 mm (7 ⅛").



# CONERO Classic Wardrobe Lift

## CONERO Classic Wardrobe Lift

Packing Unit: 1

Clear Cabinet Width (CW)*	Payload	Load capacity** (max.)	System weight (max.)	Powder Black	Champagne
445 - 628 mm (17 ½ - 24 ¾")	0-12 kg (1-26.5 lb)	14 kg (30 lb)	17.5 kg (38.5 lb)	<b>238278 7021</b>	<b>238278 9853</b>
625 - 808 mm (24 ⅝ - 31 ¾")	0-12 kg (1-26.5 lb)	14 kg (30 lb)	17.5 kg (38.5 lb)	<b>238279 7021</b>	<b>238279 9853</b>
805 - 988 mm (31 ¾ - 38 ⅞")	0-12 kg (1-26.5 lb)	14 kg (30 lb)	17.5 kg (38.5 lb)	<b>238280 7021</b>	<b>238280 9853</b>
985 - 1168 mm (38 ⅝ - 45 ⅞")	0-12 kg (1-26.5 lb)	14 kg (30 lb)	17.5 kg (38.5 lb)	<b>238281 7021</b>	<b>238281 9853</b>
805 - 988 mm (31 ¾ - 38 ⅞")	4.0-15 kg (9-33 lb)	17 kg (38 lb)	20.5 kg (45 lb)	<b>238720 7021</b>	<b>238720 9853</b>
985 - 1168 mm (38 ⅝ - 45 ⅞")	4.0-15 kg (9-33 lb)	17 kg (38 lb)	20.5 kg (45 lb)	<b>238721 7021</b>	<b>238721 9853</b>



\*The use of shims increases the necessary clear cabinet width by 30 mm (1 ⅛") each.

\*\*Load capacity = payload + 2 kg (4.5 lbs)  
(max. weight of the control lever and clothes rail).



# CONERO Classic Wardrobe Lift



- » Easily access upper clothes rails
- » Allows for the utilization of the entire closet height by swinging down the clothes rail
- » Comfortable operation with both low and full loads
- » With a payload of up to 15 kg (33 lb), even heavy jackets and coats move smoothly
- » Self-regulating power assistance allows for gentle and safe lowering even when fully loaded

**KEY**  
 CW= Clear Cabinet Width | FW= Frame Width  
 IW= Inner Width | BW= Bottom Width

