

Shown: 300192NI Brushed Nickel Finish, Etched Cased Opal Glass with Walnut Blades

$60^{\prime\prime} \; \text{Enthrall} \; \text{LED}$





INCLUDED FEATURES

Blades (5) Included

- 14° Pitch
- 60" Sweep
- Reversible
- Wood

Downrods 4" and 6" Downrod with 1" (O.D.)

Downlight Integrated. 17-W Dimmable LED Platform 1,600 Lumens, 80 CRI, 3,000K CCT

Downlight Glass Etched Cased Opal

Optional Downlight N/A

Uplight N/A

Uplight Glass N/A

Low Ceiling Adaptable Yes, Flush Mount Canopy Included

Control Wall Control System – Full Function

FAN FEATURES

Mounting Slope – Pitch 22° or 4/12 Lead Wire 78" cUL Listed Indoor Hanging Weight 23.17 lbs. Warranty Limited Lifetime

MOTOR FEATURES

Motor Size/Type 188mm x 25mm, AC Amps 0.66 on High RPM 130 on High Energy Star N/A

WAI FUL - 31 - Li Di

INCLUDED CONTROLS

WALL CONTROL SYSTEM – FULL FUNCTION


- 3 Forward Speeds & ReverseLights On/Off with Full Range
- Dimming
- Motor Off
- White Faceplate Included

OPTIONAL CONTROLS



COOLTOUCH[™] TRANSMITTER – FULL FUNCTION See pages 306-308 for more information.

COORDINATING LIGHTING



HANGING MEASUREMENTS

WITH 4" DOWNROD				
Fixture Drop (from ceiling)	Blade Drop (from ceiling)	Housing (width)	Ceiling Canopy (width)	←D→
A: 14.22"	B: 9.93" WITH 6" D	C: 12.34"	D: 6.00"	
Fixture Drop (from ceiling)	Blade Drop (from ceiling)	Housing (width)	Ceiling Canopy (width)	<u>_</u>
A: 16.22"	B: 11.93"	C: 12.34"	D: 6.00"	

AIR PERFORMANCE AIRFLOW POWER AIRFLOW EFFICIENCY USAGE 6804 80 85 Cubic Ft. Watts on High Cubic Ft. Per Minute Per Minute (Excludes Per Watt on High Lights)

