

SIDE MOUNT CAST BRASS



BBR

CENTER MOUNT



BKT

AZT

15827 BBR

15826 AZT, BKT

Kelvin	2700K – Warm White	3000K – Pure White	2700K – Warm White	3000K – Pure White
Ordering Guide & Finish	15827 BBR27R	15827 BBR30R	15826 AZT27R 15826 BKT27R	15826 AZT30R 15826 BKT30R
Housing	Cast Brass		Cast Aluminum	
Light Source	8 Integrated High Output Nichia® LEDs, tightly binned for color uniformity, and constant current driver		8 Integrated High Output Nichia® LEDs, tightly binned for color uniformity, and constant current driver	
Color Temp. (CCT) & CRI	2700K (-54/+89) / 80s CRI 3000K (-52/+122) / 80s CRI		2700K (-54/+89) / 80s CRI 3000K (-52/+122) / 80s CRI	
Power Usage at 12V AC Input VA and Watts	4.3 W, 5.8 VA		4.3 W, 5.8 VA	
Operating Voltage Range	9V-15V AC/DC with no loss in output due to constant current technology		9V-15V AC/DC with no loss in output due to constant current technology	
Lumen Maint.	Tested to an L-70 of 40,000 hours		Tested to an L-70 of 40,000 hours	
Delivered Lumens & Efficacy	2700K = 294 Lm 2700K = 67 Lm/W	3000K = 302 Lm/W 3000K = 73 Lm/W	2700K = 294 Lm 2700K = 67 Lm/W	3000K = 302 Lm 3000K = 73 Lm/W
Wiring	53" of usable #18-2, SPT-1-W leads. Cable connectors supplied.		50" of usable #18-2, SPT-1-W leads. Cable connectors supplied.	
Mounting Access. (Included)	8" slotted in-ground stake		8" slotted in-ground stake Black/White Deflector	
Optional Accessories	15601 – Surface Mounting Flange 15607 – Surface Mounting Bracket		15601 – Surface Mounting Flange 15607 – Surface Mounting Bracket FM127265 – Hexcell Louver	
Optional Lens Accessories	15677 CLR – Sprinkler Shield		N/A	
Incandescent	N/A		15326 – on page 113	
Notes	Coordinates with matching LED deck light 15765 on page 54		Coordinates with matching LED deck light 15765 on page 54	
Fixture Photometric (fc)*	Distance from Light	0' 1' 2' 3' 4' 5' 6' 7' 8'	Distance from Light	0' 1' 2' 3' 4' 5' 6' 7' 8'
	Footcandles	92.00 27.00 5.20 1.20 0.30 0.16 0.08 0.05 0.04	Footcandles	66.50 30.30 6.20 1.40 0.45 0.17 0.10 0.06 0.05
	W/Black Deflector	30.30 21.10 5.30 1.50 0.50 0.19 0.10 0.05 0.04	W/White Deflector	35.00 23.50 5.30 1.60 0.50 0.25 0.14 0.10 0.09

*Values stated for 3000K. -10% for 2700K.