

BROAD ROOF



15833 AZT

TAPERED COLUMN



15804 AZT

Kelvin	2700K – Warm White	3000K – Pure White	2700K – Warm White	3000K – Pure White														
Ordering Guide & Finish	15833 AZT27R	15833 ATZ30R	15804 AZT27R	15804 AZT30R														
Housing	Cast Aluminum with cast bottom driver compartment		Cast Aluminum with cast bottom driver compartment															
Light Source	3 Integrated High Output Nichia® LEDs, tightly binned for color uniformity, and constant current driver		6 Integrated High Output Nichia® LEDs, tightly binned for color uniformity, and constant current driver															
Color Temp. (CCT) & CRI	2700K (-54/+89) / 80s CRI 3000K (-52/+122) / 80s CRI		2700K (-54/+89) / 80s CRI 3000K (-52/+122) / 80s CRI															
Power Usage at 12V AC Input VA and Watts	4 W, 5.8 VA		1 W, 1.7 VA															
Operating Voltage Range	9V-15V AC/DC with no loss in output due to constant current technology		9V-15V AC/DC with no loss in output due to constant current technology															
Lumen Maint.	Tested to an L-70 of 40,000 hours		Tested to an L-70 of 40,000 hours															
Delivered Lumens & Efficacy	2700K = 126 Lm 2700K = 31 Lm/W	3000K = 140 Lm 3000K = 35 Lm/W	2700K = 126 Lm 2700K = 31 Lm/W	3000K = 140 Lm 3000K = 35 Lm/W														
Wiring	30" of usable #18-2, SPT-1-W leads. Cable connectors supplied.		30" of usable #18-2, SPT-1-W leads. Cable connectors supplied.															
Mounting Access. (Included)	8" slotted in-ground stake		8" slotted in-ground stake															
Optional Accessories	15601 – Surface Mounting Flange 15607 – Surface Mounting Bracket		15601 – Surface Mounting Flange 15607 – Surface Mounting Bracket															
Incandescent	N/A		N/A															
Fixture Photometric (fc)*	Distance from Light								Distance from Light									
	0'	1'	2'	3'	4'	5'	6'	7'	8'	0'	1'	2'	3'	4'	5'	6'	7'	8'
Footcandles	13.5	3.7	0.8	0.3	0.2	0.1	-	-	-	7.2	3.5	1.4	0.8	0.5	0.3	-	-	-

*Values stated for 3000K. -10% for 2700K.