

LOUVERED BOLLARD



16130 AZT, BKT

TEE BOLLARD



16131 AZT, BKT

Kelvin	2800K Warm White/Pure White	2800K Warm White/Pure White
Ordering Guide & Finish	16130AZT28 16130BKT28	16131AZT28 16131BKT28
Housing	Cast Aluminum with Weathered White Glass	Cast Aluminum with Weathered White Glass
Light Source	3 Omni-Directional Integrated High Output Nichia® LEDs, tightly binned for color uniformity utilizing remote phosphor technology, and constant current driver	3 Omni-Directional Integrated High Output Nichia® LEDs, tightly binned for color uniformity utilizing remote phosphor technology, and constant current driver
Color Temp. (CCT) & CRI	2800 (-35/+61)/CRI 80s	2800K (-35/+61)/CRI 80s
Power Usage at 12V AC Input VA and Watts	3.5W, 5.67VA	3.5W, 5.67VA
Operating Voltage Range	9V-15V AC/DC with no loss in output due to constant current technology	9V-15V AC/DC with no loss in output due to constant current technology
Lumen Maint.	Tested to an L-70 of 40,000 hours	Tested to an L-70 of 40,000 hours
Delivered Lumens & Efficacy	2800K = 224Lm 2800K = 64Lm/W	2800K = 224Lm 2800K = 64Lm/W
Wiring	20" of usable #18-2, SPT-2-W leads. Cable connectors supplied.	20" of usable #18-2, SPT-2-W leads. Cable connectors supplied.
Required Installation Accessories*	15671ST – Bollard Template Kit 15578BK – Bollard Mounting Stake	15671ST – Bollard Template Kit 15578BK – Bollard Mounting Stake
Fixture Photometric (fc)**	Distance from Light	Distance from Light
	Footcandles	Footcandles

* Customer required to purchase one for installation.

** Values stated for 2800K.