C-Series LED

120V-277V LED Small Flood, 12W & 23W



TYPE:		
ORDERING:		
COMMENTS:		

APPLICATIONS

Kichler's 120V-277V LED flood lighting fixtures are designed for outdoor lighting applications requiring uniform light sources, with long life, and little maintenance requirements.

CONSTRUCTION

Modern style with durable polyester powder coating. Vandal resistant hardware, reinforced knuckle design, a water draining front end with an integrated cowl. The accent can accept multiple media; lenses and louvers.

ELECTRICAL

UL listed for 120V-277 VAC (50/60 Hz), and suitable for wet locations. Integrated surge protection (4kV) comes standard.

OPTICS

Utilized a single LED chip-on-board light source that provides for center-to-edge uniformity and enhances beam control. NEMA 6×5 wide flood. Three-step binning for tight color consistency.

INCLUDED ACCESSORIES

Three (3) King Innovation Gel-Filled Wire Nuts

LUMEN INFORMATION

Low 16221				
Wattage	CRI	Lumens	Efficacy	L70 (hrs)
12W	80+	1000Lm	83 LPW	40,000

	High 16222					
Wattage	CRI	Lumens	Efficacy	L70 (hrs)		
23W	80+	2000Lm	87 LPW	40,000		

^{*}Lumen values same for both 3000K/4000K

LISTINGS

UL / cUL Listed - Wet Location rated IP66 - Dust & Water proof FCC Compliant

WARRANTY

6 Year Limited Warranty

ADDITIONAL MOUNTING OPTIONS





Slip-Fit Mount

Trunnion Mount

ORDERING MATRIX (Model # +Finish & CCT Codes, Version optional)

Model #	Wattage	Lumens	Finish	CCT	Version (option)
16221	12W	1000 Lm	AZT - Textured Architectural Bronze	30 - 3000k	TR - Trunnion
16222	23W	2000 Lm	BKT - Textured Black	40 - 4000k	SL - Slip-Fit


Example: 16221BKT40SL = 1000 Lm Black, Flood, 4000K, Slip-Fit



C-Series LED

120V-277V LED Small Flood, 12W & 23W

DIMENSIONS



ACCESSORIES

Ordered & shipped separately (for knuckle only)

15645 AZT, BKT - 6" StemCorrosion resistant15656 AZT, BKT - 12" Stemaluminum alloy with15657 AZT, BKT - 18" Stembaked thermoset15658 AZT, BKT - 24" Stempowder coating.

15276 BKT - Power Post: A Fast, One-Step Connector Made of Impact / Corrosion Resistant PVC 2.250" Inside Diameter to Accommodate Conduits of Different Sizes


Accepts .50 NPSM Thread

Designed For 120V-277V Line Voltage Landscape Lighting, Eliminating Need For Above or Below Ground Boxes.
Built-in Stabilizer Removes Need For Concrete


15601 AZT, BKT - Cast Aluminum Surface Mounting Flange with Bronze or Black Finish, Neoprene Gasket For Watertight Seal

15609 AZT, BKT - Junction Box Mounting Bracket Corrosion Resistant Cast Aluminum Alloy with Baked Thermoset Bronze or Black Powder Coat Finish

PHOTOMETRIC DIAGRAMS



16221BKT30 shown (1000 Lumens)



16222BKT30 shown (2000 Lumens)

