

3-Blade, 54" Ceiling Fan with Light SNB

35157 (Satin Natural Bronze)

Project Name: _____
Location: _____
Type: _____
Qty: _____
Comments: _____



Product Information

Product ID	35157
Finish	Satin Natural Bronze
Blade Finish	Rose wood

Airflow, Power and Efficiency

Speed	RPM	CFM	CFM/Watt	Amps	Watts
High	62 RPM	1089.35 cfm	115.77 cfm	0.23 A	9.41 W
Med	129 RPM	2680.07 cfm	w	0.46 A	34.78 W
Low	204 RPM	4450.32 cfm	77.06 cfm	0.69 A	82.84 W

Specifications

Number of Blades	3
Blades Included	Yes
Blade Pitch	18°
Blade Sweep	54"
Blades Reversible	No
Blade Material	ABS
Downrod 1	4.50" x 0.75" (no Thread)
Primary Control System	3-speed, manual reverse, up-down light dimmer
Remote Included	Remote Control
Lead Wire Length	54.00"
Motor Size	153MM x 20 MM
Motor Type	AC

Downlight

Downlight Included	Yes
Light Source	LED
Downlight Bulb Included	Integrated
Downlight Bulb Type	Integrated LED
Number of Lights/LEDs	1
Watts	9.41 W / 34.78 W / 82.84 W
Initial Lumens	831.5 lm
Delivered Lumens	831.5 lm
Glass Description	Opal Frosted Glass
Efficacy (LMIW)	47.84 lm/W
Kelvin Temperature	2886 K
Color Rendering Index	85.7 CRI

Notes:

- 1) Information provided is subject to change without notice. All values are design or typical values when measured under laboratory conditions.
- 2) Incandescent Equivalent: The incandescent equivalent as presented is an approximate number and is for reference only.

3-Blade, 54" Ceiling Fan with Light SNB

35157 (Satin Natural Bronze)

Project Name: _____

Location: _____

Type: _____

Qty: _____

Comments: _____

Safety Listings & Certifications

Safety Rated	Dry
Warranty	www.kichler.com/warranty

Installation

Installation requirements	The electrical junction box and support structure must be securely mounted and capable of reliably supporting a minimum of 50 pounds. Use only ETL/UL listed electrical junction boxes marked ""For Fan Support""
Electrical Requirements	120V 60Hz AC
Hanging Weight	< 50 LBS
Minimum Distance Between Bottom Of Fan Blade To Floor	7 feet

Notes:

- 1) Information provided is subject to change without notice. All values are design or typical values when measured under laboratory conditions.
- 2) Incandescent Equivalent: The incandescent equivalent as presented is an approximate number and is for reference only.