

- 1) Pass wire from fixture through stem and screw stem to top of fixture.
NOTE: Thread locking compound must be applied to all stem threads as noted with symbol (◄) to prevent accidental rotation of fixture during cleaning, relamping, etc.

2) Pass fixture wire through remaining stems and screw stems together.

3) Attach small loop to end of last stem.

4) Slip short threaded pipe through hole in canopy.

5) From inside canopy, slip lockwasher over end of threaded pipe. Screw hexnut onto end of threaded pipe.

6) Thread second small loop onto threaded pipe on canopy.

7) TURN OFF POWER.

IMPORTANT: Before you start, NEVER attempt any work without shutting off the electricity until the work is done.

a) Go to the main fuse, or circuit breaker, box in your home. Place the main power switch in the “OFF” position.

b) Unscrew the fuse(s), or switch “OFF” the circuit breaker switch(s), that control the power to the fixture or room that you are working on.

c) Place the wall switch in the “OFF” position. If the fixture to be replaced has a switch or pull chain, place those in the “OFF” position.

8) Find the appropriate threaded holes on mounting strap. Assemble mounting screws into threaded holes.

9) Attach mounting strap to outlet box. (Screws not provided). Mounting strap can be adjusted to suit position of fixture.

10) Grounding instructions: (See Illus. A or B).

A) On fixtures where mounting strap is provided with a hole and two raised dimples. Wrap ground wire from outlet box around green ground screw, and thread into hole.

B) On fixtures where a cupped washer is provided. Attach ground wire from outlet box under cupped washer and green ground screw, and thread into mounting strap.
- A**

B
- If fixture is provided with ground wire. Connect fixture ground wire to outlet box ground wire with wire connector. (Not provided.) After following the above steps. Never connect ground wire to black or white power supply wires.
- 11) Make wire connections (connectors not provided.) Reference chart below for correct connections and wire accordingly.
- | Connect Black or Red Supply Wire to: | Connect White Supply Wire to: |
|---|---|
| Black | White |
| *Parallel cord (round & smooth) | *Parallel cord (square & ridged) |
| Clear, Brown, Gold or Black without tracer | Clear, Brown, Gold or Black with tracer |
| Insulated wire (other than green) with copper conductor | Insulated wire (other than green) with silver conductor |

*Note: When parallel wires (SPT I & SPT II) are used. The neutral wire is square shaped or ridged and the other wire will be round in shape or smooth (see illus.)
- 12) Push fixture to ceiling, carefully passing mounting screws through holes in canopy.

13) Secure fixture to ceiling with knurl knobs.

14) Screw short end of threaded pipe with bead into coupling at bottom of fixture.

15) Insert recommended bulbs.

16) Set outer shade on top of glass.

17) Slip flat washer then rubber washer over end of threaded pipe.

18) Raise glass and shade up to fixture carefully passing threaded pipe through hole in glass.

19) Slip rubber washer then flat washer over end of threaded pipe. Screw finial onto end of threaded pipe. (DO NOT over tighten.)
-
- A**

B
- 11) Haga las conexiones de los alambres (no se proveen los conectores.) La tabla de referencia de abajo indica las conexiones correctas y los alambres correspondientes.
- | Conectar el alambre de suministro negro o rojo al | Conectar el alambre de suministro blanco al |
|--|--|
| Negro | Blanco |
| *Cordon paralelo (redondo y liso) | *Cordon paralelo (cuadrado y estriado) |
| Claro, marrón, amarillo o negro sin hebra identificadora | Claro, marrón, amarillo o negro con hebra identificadora |
| Alambre aislado (diferente del verde) con conductor de cobre | Alambre aislado (diferente del verde) con conductor de plata |

*Nota: Cuando se utiliza alambre paralelo (SPT I y SPT II). El alambre neutro es de forma cuadrada o estriada y el otro alambre será de forma redonda o lisa. (Vea la ilustración).
- 12) Empuje el artefacto hacia el techo, pasando cuidadosamente los tornillos de montaje a través de los orificios en el escudete.

13) Asegure el artefacto al techo con las perillas estriadas.

14) Atornille el extremo corto del tubo roscado con aislador de cuenta en el acoplamiento en la parte inferior del artefacto.

15) Inserte la lámpara recomendada.

16) Ajuste el pantalla exterior en la parte superior de la vidrio.

17) Resbale la arandela plana, luego la arandela de caucho encima del tubo roscado.

18) Levante el vidrio y la pantalla arriba hasta el artefacto. Cuidadosamente pasar el tubo roscado a través del agujero en el vidrio.

19) Resbale la arandela de caucho, luego la arandela plana encima del tubo roscado. Atornille el capuchón en el tubo roscado. (NO apriete excesivamente.)
- Date Issued: 9/2/11
- IS-65347-US