

12V 3W LED ACCENT



16000 AZT, BBR, BKT

16001 AZT, BBR, BKT, WHT

16002 AZT, BBR, BKT

Beam Spread	Beam Spread 10° Spot		Beam Spread 35° Flood		Beam Spread 60° Wide Flood	
Kelvin	2700K – Warm White	3000K – Pure White	2700K – Warm White	3000K – Pure White	2700K – Warm White	3000K – Pure White
Ordering Guide & Finish	16000 AZT27 16000 BBR27 16000 BKT27	16000 AZT30 16000 BBR30 16000 BKT30	16001 AZT27 16001 BBR27 16001 BKT27 16001 WHT27	16001 AZT30 16001 BBR30 16001 BKT30 16001 WHT30	16002 AZT27 16002 BBR27 16002 BKT27	16002 AZT30 16002 BBR30 16002 BKT30
Watts/Lumens	Compares to 10W Halogen MR16					
Housing	Cast Aluminum, Cast Brass					
Light Source	1 Integrated High Output Cree® LED, tightly binned for color uniformity, and constant current driver					
Color Temp. (CCT) & CRI	2700K (-50/+100) Warm White 3000K (-45/+130) Pure White / 80s CRI					
Optics	Radiax™ Reflector					
Power Usage at 12V AC Input VA and Watts	3W, 4VA					
Operating Voltage Range	9V-15V AC/DC with no loss in output due to constant current technology					
Lumen Maint.	Tested to an L-70 of 40,000 hours					
Delivered Lumens & Efficacy	2700K = 109 Lm 2700K = 36 Lm/W		3000K = 116 Lm 3000K = 39 Lm/W			
Wiring	24" of usable #18-2, SPT-1W leads. Wire connectors supplied. Includes LVPC installed. See page 134.					
Mounting Access. (Included)	8" slotted in-ground stake					
Optional Accessories	15601 – Surface Mounting Flange 15607 – Surface Bracket 15645, 15656, 15657, 15658 or 15570 – Stems		15609 – Junction Box Mounting Bracket 15647 – 90° Elbow			
Notes	Textured white only available in 35° beam. Brass will naturally patina over time.					