


2-IN-1 WATER ACCENT



15711 SS

Ordering Guide & Finish	15711SS27	15711SS	15711SS42
Housing	Stainless Steel housing with integrated cowl		
Light Source	1 Integrated High Output Nichia LED, tightly binned for color uniformity, and constant current driver		
Color Temp. (CCT) & CRI	2700K (-280/+0) / 80s CRI 3000K (-200/+125) / 80s CRI 4200K (-400/+400) / 80s CRI		
Optics	Custom Reflector Optic		
Power Usage at 12V AC Input VA and Watts	3.4 W, 4.9 VA		
Operating Voltage Range	9V-15V AC/DC with no loss in output due to constant current technology		
Lumen Maint.	Tested to an L-70 of 40,000 hours		
Delivered Lumens & Efficacy	2700K = 135 Lm 2700K = 40 Lm/W	3000K = 150 Lm 3000K = 44 Lm/W	4200K = 180 Lm 4200K = 53 Lm/W
Wiring	25ft of usable #18-2, SPT-2W leads		
Mounting Accessories	15776 BK – Multi-fixture weighted base. U.S. Patent Pending 15777 SS – Out-of-water bracket. U.S. Patent Pending 15778 BK – Single-fixture weighted base. U.S. Patent Pending		
Notes	Filled and sealed with two types of premium encapsulant to ensure fixture is completely watertight, 1/4-20 threaded mounting tap. Not for use with electronic transformers. Can also be used out of water as a mini accent light. Not recommended for use in salt water.		
Fixture Photometric (fc)*	Distance from Source (ft)	Illuminance (footcandles)	Beam Width (ft)
	4	5.6	3.3
	8	1.5	6.5
	16	0.4	13.0
	24	0.2	19.5
	32	0.1	26.0
	40	0.1	32.5

*Values stated for 3000K. -10% for 2700K. +25% for 4200K.



15777 SS

Stainless steel easy mount bracket (fixture sold separately) for use above ground on any surface – ideal for wood and masonry when used on decks, patios or overhangs.



15776 BK

Unique heavy weighted 3 pronged underwater accessory for 2 or 3 fixtures (sold separately) to give maximum flexibility and directional capability.



15778 BK

Heavy weight 1 prong underwater light (sold separately) accessory for standard installations. Provides advanced directional capability.