



15857 AZT - LED PIERCED DOME **15807 AZT, BBR - LED SHEPHERD'S CROOK** **15801 TZT - LED TIKI**

Description	A cast dome sculpted with a floral band and pierced to reveal a sophisticated pattern of LED light.	Traditional flare with today's LED technology.	A warm, soft center glow adds just the right hint of detail to this center mount LED path and spread.
Ordering Guide & Finish	15857 AZT - Textured Architectural Bronze (Marine grade powder coat)	15807 AZT - Textured Architectural Bronze (Marine grade powder coat) 15807 BBR - Bronzed Brass	15801 TZT - Textured Tannery Bronze™ (Marine grade powder coat)
Housing	Cast Aluminum	Cast Aluminum, Brass	Cast Aluminum
Light Source	3 Integrated High Output Nichia® LEDs, tightly binned for color uniformity, and constant current driver	3 Integrated High Output Nichia® LEDs, tightly binned for color uniformity, and constant current driver	3 Integrated High Output Nichia® LEDs, tightly binned for color uniformity, and constant current driver
Color Temp. (CCT) & CRI	3000K (-200/+125) / 80s CRI	3000K (-200/+125) / 80s CRI	3000K (-200/+125) / 80s CRI
Power Usage at 12V AC Input VA and Watts	4 W, 5.8 VA Multiply fixture VA by the number of fixtures used to determine size of transformer	High - 4 W, 5.8 VA Low - 2.5 W, 4 VA Multiply fixture VA by the number of fixtures used to determine size of transformer	4 W, 5.8 VA Multiply fixture VA by the number of fixtures used to determine size of transformer
Operating Voltage Range	9V-15V AC/DC with no loss in output due to constant current technology	9V-15V AC/DC with no loss in output due to constant current technology	9V-15V AC/DC with no loss in output due to constant current technology
Lumen Maint.	Tested to an L-70 of 40,000 hours	Tested to an L-70 of 40,000 hours	Tested to an L-70 of 40,000 hours
Total Lumens & Efficacy	3000K = 140 Lm 3000K = 35 Lm/W	3000K = 140 Lm (High), 80 Lm (Low) 3000K = 35 Lm/W (High), 20 Lm/W (Low)	3000K = 140 Lm 3000K = 35 Lm/W
Wiring	30" of useable #18-2, SPT-1W leads. Cable connector supplied	24" of useable #18-2, SPT-1W leads. Cable connector supplied	24" of useable #18-2, SPT-1W leads. Cable connector supplied
Mounting Acces. Included	8" in-ground stake	8" In-ground stake	8" In-ground stake
Optional Acces.	15601 - Surface Mounting Flange 15607 - Surface Mounting Bracket	15601 - Surface Mounting Flange 15607 - Surface Mounting Bracket	15601 - Surface Mounting Flange 15607 - Surface Mounting Bracket
Incandescent	15457 - on page 78	NA	NA
Notes	Subjected to Highly Accelerated Life Testing - 3rd party reliability testing. Not for use with electronic transformers	Subjected to Highly Accelerated Life Testing - 3rd party reliability testing. Not for use with electronic transformers	Subjected to Highly Accelerated Life Testing - 3rd party reliability testing. Not for use with electronic transformers
Fixture Photometric (fc)	Distance from Light 0' 1' 2' 3' 4' 5' 6' 7' 8' Footcandles 4.55 4.08 3.23 2.26 1.57 0.47 0.41 0.29 0.25	Distance from Light 0' 1' 2' 3' 4' 5' 6' 7' 8' Footcandles 19.9 10.7 3.56 1.45 0.57 0.26 0.14 0.08 -	Distance from Light 0' 1' 2' 3' 4' 5' 6' 7' 8' Footcandles 6.22 3.8 2.8 1.41 0.76 0.43 0.3 0.19 0.12

DESIGN PRO LED 12V PATH & SPREAD

D