

120V ACCENT

120V 19.5W
LED ACCENT



16202 AZT, BBR, WHT

16203 AZT, BBR, WHT

16207 AZT, BBR, WHT

| Beam Spread | Beam Spread 10° Spot | | Beam Spread 35° Flood | | Beam Spread 60° Wide Flood | |
|-----------------------------|---|---|---|--|---|---|
| Kelvin | 3000K – Pure White | 4250K – Cool White | 3000K – Pure White | 4250K – Cool White | 3000K – Pure White | 4250K – Cool White |
| Ordering Guide & Finish | 16202 AZT30 16202 BBR30 16202 WHT30 | 16202 AZT42 16202 BBR42 16202 WHT42 | 16203 AZT30 16203 BBR30 16203 WHT30 | 16203 AZT42 16203 BBR42 16203 WHT42 | 16207 AZT30 16207 BBR30 16207 WHT30 | 16207 AZT42 16207 BBR42 16207 WHT42 |
| Watts/Lumens | Compares to Halogen 75W PAR30 or greater | | | | | |
| Housing | Cast Aluminum, Cast Brass | | | | | |
| Light Source | 8 Integrated High Output Cree® LEDs, tightly binned for color uniformity | | | | | |
| Color Temp. (CCT) & CRI | 3000K (-45/+130) Pure White 3000K = 80s | | | 4250K (-250/+250) Cool White 4250K = 85 minimum | | |
| Optics | Radiax™ Reflector | | | | | |
| Power Usage | 19.5W, .18VA, .90pf | | | | | |
| Operating Voltage Range | 108-132V AC, 50-60 Hz | | | | | |
| Lumen Maint. | Tested to an L-70 of 40,000 hours | | | | | |
| Total Lumens & Efficacy | 3000K = 947 Lm 3000K = 49 Lm/W | | 4250K = 993 Lm 4250K = 51 Lm/W | | | |
| Wiring | 8" of usable 200° C 18AWG wire leads | | | | | |
| Mounting Access. (Included) | N/A | | | | | |
| Optional Accessories | 15276 – Power Post® 15601 – Surface Mounting Flange, for attachment to junction box 15609 – Junction Box Mounting Bracket | | | | | |
| Notes | Subjected to Highly Accelerated Life Testing – 3rd party reliability testing. Not for use with electronic transformers. *Cree is a registered trademark of Cree, Inc. Brass will naturally patina over time. | | | | | |