

12V LED/INCANDESCENT PATH & SPREAD

KENTUCKY



15393 OZ

ALMERIA™



15426 OZ

Ordering Guide & Finish	15393 OZ	15426 OZ																																								
Housing	Cast Brass with light linen glass	Aluminum and Brass with light umber glass																																								
Lamp Base	12V T5 wedge base socket	12V T5 wedge base socket																																								
Supplied Lamp	11.6-W(VA) 912X (17023) Xenon light source Power usage at 12V AC input VA MAX: 16.25-W(VA)	11.6-W(VA) 912X (17023) Xenon light source Power usage at 12V AC input VA MAX: 11.6-W(VA)																																								
Incandescent Lamp Options	16.25-W(VA) 921X (17025) 6.5-W(VA) 918X (17022) 4-W(VA) 901X (17021)	6.5-W(VA) 918X (17022) 4-W(VA) 901X (17021)																																								
LED Lamp Options	2W (18039-18041) see page 137. Compares up to 16W Xenon.	2W (18039-18041) see page 137. Compares up to 16W Xenon.																																								
Wiring	41" of usable #18-2, SPT-1-W leads. Cable connectors supplied.	34" of usable #18-2, SPT-1-W leads. Cable connectors supplied.																																								
Mounting Access. (Included)	8" In-ground slotted stake	8" In-ground slotted stake																																								
Optional Accessories	15601 – Surface Mounting Flange 15607 – Surface Mounting Bracket	15601 – Surface Mounting Flange 15607 – Surface Mounting Bracket																																								
Notes	U.S. Patent Pending. Brass will develop natural patina over time.	U.S. Patent No. D578,238. Brass will develop natural patina over time.																																								
Photometric with Supplied Lamp	<table border="1"> <tr> <td>Distance from Light</td> <td>6"</td> <td>1'</td> <td>2'</td> <td>3'</td> <td>4'</td> <td>5'</td> <td>6'</td> <td>7'</td> <td>8'</td> </tr> <tr> <td>Foot Candles</td> <td>8.96</td> <td>2.6</td> <td>.43</td> <td>.13</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> </table>	Distance from Light	6"	1'	2'	3'	4'	5'	6'	7'	8'	Foot Candles	8.96	2.6	.43	.13	-	-	-	-	-	<table border="1"> <tr> <td>Distance from Light</td> <td>0'</td> <td>1'</td> <td>2'</td> <td>3'</td> <td>4'</td> <td>5'</td> <td>6'</td> <td>7'</td> <td>8'</td> </tr> <tr> <td>Foot Candles</td> <td>10</td> <td>5.2</td> <td>.8</td> <td>.2</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> </table>	Distance from Light	0'	1'	2'	3'	4'	5'	6'	7'	8'	Foot Candles	10	5.2	.8	.2	-	-	-	-	-
Distance from Light	6"	1'	2'	3'	4'	5'	6'	7'	8'																																	
Foot Candles	8.96	2.6	.43	.13	-	-	-	-	-																																	
Distance from Light	0'	1'	2'	3'	4'	5'	6'	7'	8'																																	
Foot Candles	10	5.2	.8	.2	-	-	-	-	-																																	