



15805 BKT - LED SHALLOW SHADE - SMALL **15806 BKT - LED SHALLOW SHADE - LARGE** **15817 AZT, BN - LED GLASS & METAL**

Description	A design only made possible by today's LED technology, this fixture will surely captivate its audience with its unobtrusive styling. Coordinates with the 15806.	A design only made possible by today's LED technology, this fixture will surely captivate its audience with its unobtrusive styling. Coordinates with the 15805.	A sleek, modern original that combines contemporary style with smooth LED illumination.
Ordering Guide & Finish	15805 BKT - Textured Black (Marine grade powder coat)	15806 BKT - Textured Black (Marine grade powder coat)	15817 AZT - Textured Architectural Bronze (Marine grade powder coat) 15817 BN - Brushed Nickel
Housing	Cast Aluminum	Cast Aluminum	Aluminum (AZT) or Brass (BN) with glass diffuser
Light Source	3 Integrated High Output Nichia® LEDs, tightly binned for color uniformity, and constant current driver	3 Integrated High Output Nichia® LEDs, tightly binned for color uniformity, and constant current driver	3 Integrated High Output Nichia® LEDs, tightly binned for color uniformity, and constant current driver
Color Temp. (CCT) & CRI	3000K (-200/+125) / 80s CRI	3000K (-200/+125) / 80s CRI	3000K (-200/+125) / 80s CRI
Power Usage at 12V AC Input VA and Watts	4 W, 5.8 VA Multiply fixture VA by the number of fixtures used to determine size of transformer	4 W, 5.8 VA Multiply fixture VA by the number of fixtures used to determine size of transformer	4 W, 5.8 VA Multiply fixture VA by the number of fixtures used to determine size of transformer
Operating Voltage Range	9V-15V AC/DC with no loss in output due to constant current technology	9V-15V AC/DC with no loss in output due to constant current technology	9V-15V AC/DC with no loss in output due to constant current technology
Lumen Maint.	Tested to an L-70 of 40,000 hours	Tested to an L-70 of 40,000 hours	Tested to an L-70 of 40,000 hours
Total Lumens & Efficacy	3000K = 140 Lm 3000K = 35 Lm/W	3000K = 140 Lm 3000K = 35 Lm/W	3000K = 140 Lm 3000K = 35 Lm/W
Wiring	30" of useable #18-2, SPT-1W leads Cable connector supplied	30" of useable #18-2, SPT-1W leads Cable connector supplied	30" of useable #18-2, SPT-1W leads Cable connector supplied
Mounting Acces. Included	8" in-ground stake	8" In-ground stake	8" In-ground stake
Optional Acces.	15601 - Surface Mounting Flange 15607 - Surface Mounting Bracket	15601 - Surface Mounting Flange 15607 - Surface Mounting Bracket	15601 - Surface Mounting Flange 15607 - Surface Mounting Bracket
Incandescent	NA	NA	15317 - on page 92
Notes	Subjected to Highly Accelerated Life Testing - 3rd party reliability testing. Not for use with electronic transformers	Subjected to Highly Accelerated Life Testing - 3rd party reliability testing. Not for use with electronic transformers	Subjected to Highly Accelerated Life Testing - 3rd party reliability testing. Not for use with electronic transformers
Fixture Photometric (fc)	Distance from Light 0' 1' 2' 3' 4' 5' 6' 7' 8' Footcandles 21.2 12.1 5.3 1.56 .23 .33 .11 .06 -	Distance from Light 0' 1' 2' 3' 4' 5' 6' 7' 8' Footcandles 20.7 11.1 4.8 1.56 0.55 0.33 0.11 0.06 -	Distance from Light 0' 1' 2' 3' 4' 5' 6' 7' 8' Footcandles 5.47 6.07 3.87 2.12 1.17 0.77 0.38 0.16 0.04