

Recreational Fire Extinguisher – FA110G

Part number 466142MTL

Multipurpose use

Disposable

UL Rated 1-A:10-B:C



Description

Suitable for use on Class A (trash, wood & paper), Class B (liquids & gases) and Class C fires (energized electrical equipment).

The Recreational unit is fitted with a pressure gauge that provides at-a-glance status, is manufactured from lightweight aluminum and a tough aluminum valve assembly.



Includes plastic strap bracket (322057)


At a Glance

- Model FA110G
- Multipurpose Dry Chemical
- UL listed
- UL rated 1-A,10-B:C
- USCG, DOT approved
- Supplied with retention strap bracket
- Monoammonium Phosphate
- 6 year limited warranty
- Suitable for use on most common fires

Features

- Easy-to-read gauge tells you fire extinguisher is charged and ready for use
- Clear instruction label using graphics to show steps required to operate extinguisher
- Easy-to-pull safety pin
- Rust and impact resistant steel handle
- 2.5 lb. of fire extinguishing agent (Average)
- 6 year limited warranty
- UL approved strap retention bracket
- Coast Guard (USCG) approved when fitted with supplied mounting bracket

For use on the following types of fire:



P/N: 466142MTL - 6 pack
 UPC: 0-47871-27002-6
 I2F - 10047871270023

Product Specification

Net agent weight (Average)	2.5 lb.
Unit weight (Average)	3.9 lb.
Diameter	3.25 inches
Height	14.2 inches
Discharge time	8-12 seconds
Discharge range	6-8 feet
Operating pressure	100 psi
Cylinder	Seamless aluminum
Valve, handle, lever	Aluminum and steel
Strap Bracket	USCG approved

Packaging Options



MASTER PACK

Packaging dimensions (inches)

	Depth	Width	Height
Carton	4.25	3.375	14.31
Master Pack	21.37	9.5	14.37

This information is subject to change without notice. Kidde Fire Safety disclaims any liability for any errors or misinterpretations of the information contained therein. Contact Kidde Fire Safety or your local distributor for assistance.

Kidde Fire Safety

1016 Corporate Park Drive, Mebane, NC 27302
 (800) 880-6788 www.Kidde.com

