



Features

- End drain.
- Two-piece design.
- Integral lumbar support and armrests for comfort.
- Slotted overflow for maximum bathing depth
- Textured bottom surface.
- 6 transducers and control amplifier create surround sound experience that gently massages the body
- High-resolution color screen in polished chrome.
- 61-3/4" (1568 mm) x 31-3/4" (806mm) x 22" (559 mm)

Material

- Acrylic

Hydrotherapy

- VibrAcoustic® technology emits sound waves and offers a surround sound experience.

Installation

- Freestanding
- Syncs with devices enabled with BLUETOOTH® wireless technology including smart phones, MP3 players, tablets and laptops located up to 33 feet away.*

Required Accessories

K-7271 Brass Slotted Overflow Bath Drain

or

K-7272 PVC Slotted Overflow Bath Drain

Components

Additional included component/s: 25' (7.6 m) cables.



Codes/Standards

CSA B45.5/IAPMO Z124

UL 1795

CSA C22.2 No. 218.2

Greenguard UL 2818 - Gold

CARB P2

KOHLER® One-Year Limited Warranty

See website for detailed warranty information.


*The BLUETOOTH® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by Kohler Co. is under license. Other trademarks and trade names are those of their respective owners.

Available Color/Finishes

Color tiles intended for reference only.

Color	Code	Description
	0	White
	96	Biscuit
	47	Almond
	NY	Dune
	G9	Sandbar

No change in measurements if connected with drain illustrated. (K-7272)
Faucet area.



Required Electrical Service

One dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI) or Residual Current Device (RCD).

Amplifier: 120 V, 15 A, 60 Hz

Technical Information

All product dimensions are nominal.

Installation: Freestanding
 Drain location: End
 Basin area, bottom: 45-1/8" x 19-11/16" (1147 mm x 500 mm)
 Basin area, top: 52-3/4" x 25-5/16" (1339 mm x 643 mm)
 Weight: 171 lbs (77.6 kg)
 Minimum floor load: 43.5 lbs/ft² (212.4 kg/m²)
 Water depth: 15-1/16" (383 mm)
 Water capacity: 58 gal (219.6 L)
 Template: Footprint, 1265460, not required, not included
 Electrical component rating: Amplifier: 120 V, 1.1 A, 50/60 Hz
 Amplifier channels: 2 at 15 W per channel, 2 at 30 W per channel

Notes

Measure your actual product for rough-in details. Install this product according to the installation instructions. The hot water supply should be 70% of the capacity of the bath or greater. Installations will vary. Provide one grounded electrical outlet within 24" (610 mm) of each component. Control amplifier fits 16" (406 mm) center studs.