

Rite-Temp® bath and shower trim kit, 1.75 gpm K-TS23502-4G

Features

- Pressure-balancing diaphragm technology maintains outlet temperature within +/-3°F during water pressure fluctuations
- Antiscald protection
- A single handle controls both on/off activation and temperature setting
- 6-1/4" (159 mm) diverter bath spout with slip-fit connection
- 1.75 gpm (6.6 lpm) showerhead with Katalyst® air-induction technology
- MasterClean[™] sprayface features an easy-to-clean surface that withstands mineral buildup
- Coordinates with other products in the Parallel collection

Material

- Premium material construction with metal handle ensures reliability and durability
- KOHLER® finishes resist corrosion and tarnishing

Technology

 Katalyst® air-induction technology infuses water with air, creating bigger drops for a more powerful spray

Installation

Trim only; requires valve to complete installation (sold separately)

Required Products/Accessories

K-8304 Series Rite-Temp ${\ensuremath{\mathbb R}}$ Valve & Cartridge Kits or


K-8300 Series Rite-Temp® Valve Body Rough-ins K-8305 Series Rite-Temp® Cartridges

Recommended Products/Accessories

K-23723 Faucet cleaner

Optional Products/Accessories

K-10351 Test cap for K-8300 Series valve bodies 1307346 Retro mixer cap for K-304 Rite-Temp valve 1362395 Retro mixer cap for K-2971 HiFlow Rite-Temp valve K-10350 Deep rough-in kit





Codes/Standards

ASME A112.18.1/CSA B125.1 DOE - Energy Policy Act 1992 EPA WaterSense® California Energy Commission (CEC)

KOHLER® Faucet Lifetime Limited Warranty

See website for detailed warranty information.

Available Colors/Finishes

Color tiles intended for reference only.

Color Code Description




- CP Polished Chrome
- BN Vibrant® Brushed Nickel
- BL Matte Black

2MB Vibrant® Brushed Moderne Brass

KOHLER, Faucets

Parallel® Rite-Temp® bath and shower trim kit, 1.75 gpm K-TS23502-4G



Technical Information

All product dimensions are nominal. No

Drain included:

Spout:

Spout reach: 6-1/4" (158 mm)

Showerhead/Body Spray:

Rated maximum 1.75 gal/min (6.6 l/min) flow: Pressure: 45 psi (3.1 bar)

Notes

Install this product according to the installation instructions.

