# **KOHLER**<sub>®</sub>

### Highline® Two-piece elongated toilet, 1.6 gpf K-43979-RA

### Features

- Two-piece design
- Right-hand Polished Chrome trip lever
- Elongated bowl offers added room and comfort
- Comfort Height® feature offers chair-height seating that makes sitting down and standing up easier for most adults
- 1.6 gpf (6.0 lpf)
- 2-1/8" (54 mm) fully glazed trapway
- Revolution 360<sup>®</sup> flushing technology generates a forceful swirling motion to keep the bowl clean longer
- Sanitary guard where bowl and tank meet for ease of cleaning
- Weighs less than previous Highline models
- Combination consists of K-44199 bowl and K-44468-RA tank
- AquaPiston® canister optimizes the flow out of the tank, harnessing gravity and the natural, powerful reducing cascade of water to increase the power and effectiveness of the flush
- Easy-to-flush canister design requires less force to actuate than a 3" (76 mm) flapper, and has 90% less exposed seal material which resists conditions that cause wear, tear, shrinkage and swelling

### Installation

- Standard 12" (305 mm) rough-in
- Seat and supply line sold separately

### **Recommended Products/Accessories**

K-44199 Elongated toilet bowl K-44468-RA Toilet tank, 1.6 gpf K-4636-RL Cachet® ReadyLatch® Quiet-Close™ elongated toilet seat K-18751 PureWash® E525 Elongated bidet toilet seat K-9379 Trip Lever K-23726 Drain treatment

### **Included Components**

K-44199 Elongated toilet bowl K-44468-RA Toilet tank, 1.6 gpf





### **Codes/Standards**

ASME A112.19.2/CSA B45.1 DOE - Energy Policy Act 1992 ADA ICC/ANSI A117.1 CSA B651 OBC

# KOHLER<sup>®</sup> Toilets and Seats Limited Warranty

See website for detailed warranty information.

#### **Available Colors/Finishes**

Color tiles intended for reference only.

**Color Code Description** 

0 White





### Highline® Two-piece elongated toilet, 1.6 gpf K-43979-RA



### **Technical Information**

## All product dimensions are nominal.

rollet type.	FIOOF-MOUNT
Waste Outlet:	Floor
Flush type:	AquaPiston
Trap passageway:	2-1/8" (54 mm)
Rim to water	6-9/16" (166 mm)
surface:	
Rough-in:	12" (305 mm)

### Notes

Install this product according to the installation instructions.

ADA, OBC, CSA B651 compliant when installed to the specific requirements of these regulations.

Plumbing codes may require elongated toilets and elongated, open-front seats in public bathrooms.

Accessibility standards may require controls to be located on the open side of the toilet.

