

Product Information

Applicable product:	
Bath whirlpool, custom pump	K-1170-HC
Bath whirlpool, custom pump	K-1170-HE
Bath whirlpool, custom pump	K-1170-HH
Bath whirlpool, custom pump	K-1170-HN

Fixture*:	
Basin area:	
Bathing well	42" (106.7 cm) x 27" (68.6 cm)
Top area	54" (137.2 cm) x 30" (76.2 cm)
Weight	134 lbs (60.8 kg)
To overflow:	
Water depth	16" (40.6 cm)
Capacity	81 gal (306.6 L)
* Approximate measurements for comparison only.	

Drop-in cut-out	64-1/2" (163.8 cm) x 40-1/2" (102.9 cm)
-----------------	---

Pump:	kW	V	Hz	A
	1.5	240	50/60	11

Required Electrical Service

Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI) or Residual Current Device (RCD):	
Pump/control	220/240 V, 20 A, 50/60 Hz

Installation Notes

Install this product according to the installation guide.

Floor support under whirlpool must provide for a minimum of 44 lbs/square foot (212 kg/square meter) loading.

Hot water supply should be 70% of capacity or greater. Installations will vary.

If installing a rim-mount faucet, make sure there is no interference with drain overflow and circulating system before drilling any holes. Consult local and national codes for minimum air gap requirements if installing a spout on the faucet deck.

This whirlpool is designed for drop-in installation only. It is not suited for use in a three wall alcove with an overhead shower.

Pump must be relocated to custom position at the time of installation. Provide adequate clearance.

Fixture conforms to ANSI Standard Z124.1.2. All dimensions are nominal.

