

### Product Information

Applicable products:			
Bath whirlpool – drop-in	K-1126		
Bath whirlpool – tile flange, left drain	K-1126-L		
Bath whirlpool – tile flange, right drain	K-1126-R		
Fixture*:			
Bathing well:			
Basin area, bottom	46" (116.8 cm) x 21" (53.3 cm)		
Basin area, top	55" (139.7 cm) x 31" (78.7 cm)		
Weight	67.5 lbs (30.6 kg)		
To overflow:			
Water depth	14" (35.6 cm)		
Capacity	57 gal (215.8 L)		
* Approximate measurements for comparison only.			
Drop-in cut-out	58-1/4" (148 cm) x 40-1/2" (102.9 cm)		
Pump:	V	Hz	A
1-speed	120	60	7.5

### Required Electrical Service

Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI):	
Pump/control	120 V, 15 A, 60 Hz
Locate the outlet behind the whirlpool and within 24" (61 cm) of the pump.	

### Installation Notes

Install this product according to the installation guide.

Floor support under whirlpool must provide for a minimum of 33 lbs/square foot (159 kg/square meter) loading.

The apron must be installed before the finished floor and wall materials are installed.

No change in measurements if connected with drain illustrated. (K-1167 or K-1167M)

Fixture conforms to ANSI Standard Z124.1.2. All dimensions are nominal.

