

Product Information

| | | |
|---|---------------------|-------------|
| Mexico products have an M after the first sequence of numbers (such as K-12345 M). | | |
| Applicable product: | | |
| Seat on right | K-12109 | shown |
| Seat on left | K-12110 | not shown |
| Fixture: | 230 lbs. (104.3 kg) | |
| Configuration | 1-piece | |
| Drain outlet | 3-3/8" D. (8.6 cm) | |
| Accessories/hardware: | | |
| Drain | K-9132 | recommended |
| Dome light | K-1665 | optional |

Installation Notes

Install this product according to the installation guide.

For increased accessibility, utilize "pit" installation as detailed in instructions.

For optimum accessibility, specify faucets and fittings to install and operate within the control area shown.

The fixture is not drilled for supply fittings.

Shimming may be required to level the fixture.





Stud opening tolerance is + 1/4" (6 mm), - 0" (0 mm).

When fire rated construction is specified, dimensions are to the inside of the fire-rated wall.

Some shimming between stud frame and fixture may be required.

Provide clear floor space per ICC/ANSI A117.1 and as shown.

This fixture conforms to ANSI Standard Z124.2. All dimensions are nominal.

| | |
|--|--|
| *Recess opening must be 52-1/4" (132.7 cm) x 84-1/4" (214 cm). | |
| No change in measurements if connected with drain illustrated. (K-9132) | |
|  | Represents control area for faucets |
|  | Represents 24" (61 cm) wall mount slide bar. |
|  36" (91.4 cm) 43" (109.2 cm) | Represents clear floor space for 36" (91.4 cm) x 43" (109.2 cm) side entrance. |
|  48" (121.9 cm) 43" (109.2 cm) | Represents clear floor space for 48" (121.9 cm) x 43" (109.2 cm) front entrance. |

