

Product Information

| | |
|---|---------------------------------|
| Applicable product: | |
| 5' x 21" bath whirlpool | K-1487-H2 |
| Fixture*: | |
| Bathing well: | |
| Basin area | 41" (104.1 cm) x 29" (73.7 cm) |
| Top area | 56" (142.2 cm) x 36" (91.4 cm) |
| Weight | 140 lbs (63.5 kg) |
| To overflow: | |
| Water depth | 15" (38.1 cm) |
| Capacity | 85 gal (321.8 L) |
| * Approximate measurements for comparison only. | |
| Drop-in cutout | 58" (147.3 cm) x 40" (101.6 cm) |
| Pump: | kW V Hz A |
| Variable-speed: | 1.5 240 50/60 11 |
| Required accessories: | |
| Jet trim kit | K-9696 |

Required Electrical Service

Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI) or Residual Current Device (RCD):

| | |
|--------------|---------------------------|
| Pump/control | 220/240 V, 20 A, 50/60 Hz |
|--------------|---------------------------|

Locate the outlets behind the whirlpool and within 24" (61 cm) of the pump.

Installation Notes

Install this product according to the installation guide.

NOTE: Pump protrusion beyond rim.

Floor support under whirlpool must provide for a minimum of 51 lbs/square foot (248 kg/square meter) loading.

Hot water supply should be 70% of capacity or greater. Installations will vary.

If installing a rim-mount faucet, make sure there is no interference with drain overflow and circulating system before drilling any holes. Consult local and national codes for minimum air gap requirements if installing a spout on the faucet deck.

This fixture conforms to ANSI Standard Z124.1.2. All dimensions are nominal.

Note: Pump Protrusion Beyond Rim

No change in measurements if connected with drain illustrated. (K-7161-AF or K-7161M-AF)

