

Product Information

Applicable product:				
Bath whirlpool, custom pump	K-1487-HF			
Bath whirlpool, custom pump	K-1487-HH			
Bath whirlpool, custom pump	K-1487-HM			
Bath whirlpool, custom pump	K-1487-HN			
Fixture*:				
Bathing well:				
Basin area	41" (104.1 cm) x 29" (73.7 cm)			
Top area	56" (142.2 cm) x 36" (91.4 cm)			
Weight	140 lbs (63.5 kg)			
To overflow:				
Water depth	15" (38.1 cm)			
Capacity	85 gal (321.8 L)			
* Approximate measurements for comparison only.				
Drop-in cutout	58" (147.3 cm) x 40" (101.6 cm)			
Pump:	kW	V	Hz	A
Variable-speed:	1.5	240	50/60	11

Required Electrical Service

Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI) or Residual Current Device (RCD):	
Pump/control	220/240 V, 20 A, 50/60 Hz

Installation Notes

Install this product according to the installation guide.

Floor support under whirlpool must provide for a minimum of 51 lbs/square foot (248 kg/square meter) loading.

Hot water supply should be 70% of capacity or greater. Installations will vary.

Pump must be relocated to custom position at the time of installation. Provide adequate clearance.

If installing a rim-mount faucet, make sure there is no interference with drain overflow and circulating system before drilling any holes. Consult local and national codes for minimum air gap requirements if installing a spout on the faucet deck.

This fixture conforms to ANSI Standard Z124.1.2. All dimensions are nominal.

No change in measurements if connected with drain illustrated. (K-7161-AF or K-7161M-AF)

