

Product Information

Applicable product:	
Elongated bowl toilet – classic design	K-3451
Elongated bowl toilet – stately design	K-3453
ADA compliant (when installed following installation notes).	ADA

Fixture:	
Configuration	one-piece, compact elongated
Water per flush	1.6 gal (6 L) or 1.4 gal (5.3 L)
Passageway	2-1/8" (5.4 cm)
Water area	10-3/4" (27.3 cm) x 8-1/4" (21 cm)
Water depth from rim	6" (15.2 cm)
Seat post hole centers	5-1/2" (14 cm)

Included components:	
Closed front seat with cover	K-4733
Tank cover – classic design OR	88871
Tank cover – stately design	88872
Trip lever	K-9477
Bolt cap accessory pack	52048
Tank accessory pack	52265

Installation Notes

Install this product according to the installation guide.

Will comply with the American Disabilities Act (ADA) when installed per the requirements of the Accessibility Guidelines, Section 604 Water Closets, of the Act, which include the installation of an open front seat.

Section 604 states the required height of the toilet is 17" (43.2 cm) to 19" (48.3 cm) from the floor to the top of the seat to meet ADA requirements.

Fixture conforms to ASME Standard A112.19.2/CSA B45.1. All dimensions are nominal.

